

# HALE TRAILER BRAKE & WHEEL



## Hale Trailer Brake & Wheel 576523-576524

Renegade LXLN 12 Air Tandem (Model: RENEGADELXLN12)	
	Est. Wt.: 20830# +/- 3%
<b>Capacity:</b> 30 tons in 16-foot length - GAWR and tire ratings determine legal loads -30 tons in 20-foot with 3rd axle	
<b>Load Base:</b> 16-foot rigid 2-point load centered in deck	
<b>Framework:</b> All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
<b>Compatibility:</b> Low profile 3rd axle optional	
<b>Length / Width:</b> 53 feet 0 inches - 102 inches wide	
<b>Gooseneck Design:</b> Narrow hydraulic removable non-ground bearing - swing radius of 84 inches (11 ft 2 in overall gooseneck length) - set up for wet line operation	
<b>Loaded Fifth Wheel Height:</b> 50 in nominal loaded fifth wheel height via dual cam pawl arm assembly with 7 ride height positions	
<b>Power Source:</b> 13Hp gasoline powered auxiliary power unit REV 1 12-18-18	
<b>Electrical Receptacle:</b> J560 7-pin connector	
<b>Deck Design:</b> Flat level deck design	
<b>Deck Length:</b> 32 feet 11 inches clear deck length	
<b>Loaded Deck Height:</b> 12 inches with 4 inch ground clearance (Fully Loaded)	
<b>Crossmembers:</b> On 18 inch centers	
<b>Flooring:</b> 1 3/8 inch nominal Apitong wood (full width)	
<b>Recessed Floor Mounted D-Ring Package:</b> None	
<b>Front Ramps:</b> None, front of deck sloped top down to assist in loading with traction cleats	
<b>Extension Brackets:</b> None	
<b>Front Bogie Ramp:</b> Sloped steel bogie ramp (full width)	
<b>Mini Boom Trough &amp; Traction Cleats:</b> None	
<b>Deck to Bogie Connection:</b> Fixed	
<b>Number of Axles:</b> 2	
<b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
<b>Axle Spread:</b> 50 inches (between axles)	
<b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
<b>Spring Brakes:</b> Spring brakes (2 axles)	
<b>Dust Shields:</b> None	
<b>Suspension:</b> Air ride with automatic controls	
<b>Tires:</b> 255/70R 22.5 H ply OEM Standard	
<b>Tire Brand:</b> OEM Standard	
<b>Wheels:</b> 8.25 x 22.5 steel disc - hub-piloted	
<b>Covered Rear Bogie:</b> Rear bogie platform with 1 1/8 inch wood floor	
<b>Rear Bogie Height:</b> 41.5 inches	
<b>Bumper:</b> 3 tail light package	
<b>Connections for Future Axle Attachment:</b> Air and electrical connections to go along with connecting ears	
<b>Width:</b> 8 feet 6 inches	
<b>Electrical System:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
<b>Flip Axle:</b> None	
<b>Dust Shields on Flip Axle:</b> None	
<b>Paint:</b> Special paint Orange (paint to be approved by dealer) REV 1 12-18-18	
<b>Lash Rings:</b> 12 pair - 24 total	

<b>Flag Holders:</b> 2 pair flag holders	
<b>ABS:</b> 4S/2M system without diagnostic tool and cable	
<b>Liquid Filled Gauge:</b> Standard	
<b>Marker Lights:</b> 6 marker lights per side including mid-turn	
<b>VIN Plate:</b> Bilingual VIN plate	
<b>Registration/Document Holder:</b> Install registration/document holder	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.