



Hale Trailer Brake & Wheel 576527-576529

| Magnitude 452 Jeep (Model: SC452JEEP) | |
|---|------------------------|
| | |
| | Est. Wt.: 8350# +/- 3% |
| Capacity: 45 Tons GAWR and tire rating determine legal loads | |
| Framework: All main longitudinal members fabricated with 100,000 PSI minimum yield steel flanges with 50,000 PSI webs | |
| Compatibility: Magnitude 70 80 90 Class | |
| Gooseneck Design: Fixed narrow | |
| Loaded Fifth Wheel Height: 50 inches | |
| Swing Radius: 104 and 80 inches (removeable) | |
| Electrical Receptacle: J560 7-pin connector | |
| Deck Design: Beam design | |
| Fifth wheel: Sliding fifth wheel with a 55 inch fifth wheel height (54 inch slide) Extra Long 5 th wheel slider | |
| Deck to Bogie Connection: Fixed | |
| Number of Axles: 2 | |
| Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components. | |
| Axle Spread: 60 inches (between axles) | |
| Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount | |
| Dust Shields: None | |
| Suspension: Air ride | |
| Tires: 275/70R 22.5 H ply OEM Standard | |
| Wheels: 8.25 x 22.5 steel disc - hub-piloted | |
| Width: 8 feet 6 inches | |
| Electrical System: DOT sealed beam and harness | |
| Paint: Fontaine black polyurethane enamel | |
| ABS: Not required | |
| Flip Axle: None | |
| Registration/Document Holder: Install registration/document holder | |