



Hale Trailer Brake & Wheel

578212-578214

Renegade LXTN40 Air Tandem (Model: RENEGADELXTN40)	
	Est. Wt.: 22490# +/- 3%
Capacity: 40 tons in 16-foot length - GAWR and tire ratings determine legal loads	
Load Base: 16-foot rigid 2-point load centered in deck	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Compatibility: Designed to accept 3rd flip axle - none	
Length / Width: 50 feet 1 inch - 102 inches wide	
Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11 ft 11 in overall gooseneck length) - set up for wet line operation	
Loaded Fifth Wheel Height: 50 in nominal loaded fifth wheel height with 5 ride height positions	
Power Source: None	
Electrical Receptacle: J560 7-pin connector	
Deck Design: Flat level telescopic deck design	
Deck Length: 29 feet 0 inches clear deck length (retracted) - 50 feet 0 inches (extended)	
Loaded Deck Height: 20 inches with 6 inches ground clearance	
Flooring: 1 3/8 inch nominal wood (full width)	
Recessed Floor Mounted D-Ring Package: None	
Crossmembers: On 24 inch centers	
Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats	
Extension Brackets: Outriggers - 14 pair - 28 total removable swing type, 1 pair - 2 total removable hook-on type	
Front Bogie Ramp: Sloped steel bogie ramp (full width)	
Mini Boom Trough & Traction Cleats: None	
Deck to Bogie Connection: Fixed	
Number of Axles: 2	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 54.5 inches spread (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Dust Shields: None	
Spring Brakes: Spring brakes on 2 axles	
Suspension: Air ride with automatic controls	
Tires: 255/70R 22.5 H ply OEM Standard	
Wheels: 8.25 x 22.5 steel disc - hub-piloted	
Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor	
Rear Bogie Height: 41 inches	
Bumper: 3 tail light package	
Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears	
Width: 8 feet 6 inches	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Flip Axle: None	
Dust Shields on Flip Axle: None	
Paint: Fontaine black polyurethane enamel	
Lash Rings: 12 pair - 24 total	

Flag Holders: 2 pair flag holders	
ABS: 4S/2M system without diagnostic tool and cable	
Liquid Filled Gauge: Included	
Marker Lights: 8 marker lights per side including mid-turn	
Accent Package: Stainless steel bumper insert	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Install registration/document holder	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.