



# Hale Trailer Brake & Wheel

## 856416-856424



<input checked="" type="checkbox"/> Flat Extendable	<input checked="" type="checkbox"/> Drop
Length : 53' to 218' with bumper	
Width : <input checked="" type="checkbox"/> 102"	
Steering axles : <input checked="" type="checkbox"/> 3	
Suspension : <input checked="" type="checkbox"/> Turner HT-250U	
<input checked="" type="checkbox"/> Scale-O-Matic	<input checked="" type="checkbox"/> COLAS Valve
<input checked="" type="checkbox"/> Shut-off valve	
Axle Location :	
Steering mecanism :	
<input checked="" type="checkbox"/> Forced steer with front turn table	
<input checked="" type="checkbox"/> Suspension and axles with turn tables	
Steering control : <input checked="" type="checkbox"/> Automatic <input checked="" type="checkbox"/> Manual	
<input checked="" type="checkbox"/> 13 HP Honda power pack	
Axles : <input checked="" type="checkbox"/> D-22 <input type="checkbox"/> F-24 for 17,5 wheels	
Axle track : <input checked="" type="checkbox"/> Other : 79	
Brake type: <input checked="" type="checkbox"/> Drum brakes	
Seals : Stemco Guardian HP	Bearings : Stemco
Brake Chambers: TSE 30/30T	
Automatic Slack adjuster : <input checked="" type="checkbox"/> TSE	
Brake valve : Rockwell Wabco	
A.B.S. Brake : <input checked="" type="checkbox"/> 2S/1M	
<input checked="" type="checkbox"/> Blue wire on first axle	A.B.S. Plug <input type="checkbox"/> Y <input checked="" type="checkbox"/> N
Hubs : <input checked="" type="checkbox"/> Dura Light 8 studs steel piloted hubs	
Drums : <input checked="" type="checkbox"/> Standard	
Rims : Qty : 12	
<input checked="" type="checkbox"/> 17.5 x 6.75	<input checked="" type="checkbox"/> Alum. machined finish
<input checked="" type="checkbox"/> Plastic spacer (rim & rim)	<input checked="" type="checkbox"/> Plastic spacer (hub & rim)
Tires : Qty : 12	
Model: Michelin XTA2 ENERGY Size : 245/70R17.5	
Tire carrier Témisko Fab :	
<input checked="" type="checkbox"/> 1	<input checked="" type="checkbox"/> C/S
Hubodometer : <input checked="" type="checkbox"/> None	
Location :	
Paint : Colour : Black	<input checked="" type="checkbox"/> Tape 100%
Trim : <input checked="" type="checkbox"/> None	
Rim : <input checked="" type="checkbox"/> Natural	
Rack : <input checked="" type="checkbox"/> None	

Fifth wheel height : 48
King Pin <input checked="" type="checkbox"/> Other : 28.5
Location : <input checked="" type="checkbox"/> Bolt-on
Coupler
Plate: <input checked="" type="checkbox"/> 1/2" HTS
Gooseneck: <input checked="" type="checkbox"/> Hinged
Frame : Extendable with camber
Extendable boxed beams (caisson): <input checked="" type="checkbox"/> 3+1
Removable blade support on beams: <input checked="" type="checkbox"/> 1
X-Member : Fabricated special
Nose corners : <input checked="" type="checkbox"/> 45°
Side Rail :
Rub rail :
<input checked="" type="checkbox"/> None
Stake pocket : <input checked="" type="checkbox"/> None
At front bolster : <input checked="" type="checkbox"/> N
At rear bolster :
Winches : Total : _____ <input checked="" type="checkbox"/> None
<input type="checkbox"/> Recessed <input type="checkbox"/> Bolt-on
Quantity R/S _____ Quantity C/S _____
Distance from front _____
Sliding track :
Floor : <input checked="" type="checkbox"/> Other : Steel covered with rubber
Bumper : <input checked="" type="checkbox"/> Long <input checked="" type="checkbox"/> Steel Extendable 20'
Fenders : Plastic over axles <input type="checkbox"/> Other :
Mud flaps : <input checked="" type="checkbox"/> Témisko
Location : Back of gooseneck and at each axle
Land. gear : <input checked="" type="checkbox"/> Holl. Mark V
Crank : <input checked="" type="checkbox"/> R/S
Lights : <input checked="" type="checkbox"/> Truck-lite round type (2/s) <input checked="" type="checkbox"/> 45° flasher
<input checked="" type="checkbox"/> LED lights
<input checked="" type="checkbox"/> Other: Beacon light at rear bumper
Strobe lights in bumper on switch (clearance cuircuit)
Title hold :
Location : <input checked="" type="checkbox"/> Truck-lite
Tool box : <input checked="" type="checkbox"/> Alum. Témisko FAB
Dimensions : 25" X 24" X 48"
Location : In front of tridem, on both sides

- Visual lock indicators for inter beam locking
- Aluminum checkerplate on front coupler, Aluminum checkerplate front fenders
- (4) supports for air and hydraulic lines/beam
- Power pack in aluminum box on R/S
- Double redundant hydraulic steering circuit.
- On board steering control, Plug in remote control and wireless remote control (Lodar) + antenna
- dual Hydraulic drop leg to facilitate extending
- "D" rings on each side of the front and rear loading platforms
- 180 ft of hydraulic lines from front to back
- Oversized sign at rear

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

**Special**