



Hale Trailer Brake & Wheel

001027



20ART

20 Ton Tandem Air Tilt/Air Ramp

Tags

Base Weight: 11,020

TRAILER

Overall Length 34 ft. 6 in.
Overall Width 102 in.
Weight lbs +/- 2% 11136, including options
A-Frame 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
Hitch 3 in. pintle eye, adjustable 5 position 17 in. to 28 in.

DECK

Deck Length 21 ft.
Loaded Deck Height 34 in.
Main Frame Hi-Tensile Wide Flange 14 in. @ 22
Cross Members Hi-Tensile 6 in. Channel @ 8.2
Side Rail Hi-Tensile 8 in. Channel @ 11.5 open on inside
Air Tilt Deck 2 Air Bags
Floor 1 3/8 in. x 7 in. Keruing Shiplapped
Landing Gear Dual 2 Speed

SUSPENSION/AXLES

Axles 25,000 lbs Capacity 77.5 in. Track 3/4 in. wall
Spread 49 in.
Suspension Hutch 9700 spring ride
Brakes Quick Change 12 1/4 in. x 7 in.
Brake Chamber #3030, All Axles
Air Brake System 2S/1M
Bearings Oil Bath
Slack Adjusters Automatic
Hubs & Drums 8 Stud Unimount C / W Cast Drums
Tires Tire Upgrade to 235/75R17.5
Wheels 6.75 x 17.5 Steel Disc - Painted White

BEAVERTAIL

Length 6 ft. @ 6 degree slope, Planked in

RAMPS

Length 38 in. x 76 in. Air Operated Planked

GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue
Lights LED CMVSS 108 / FMVSS 108
Front Connector SAE J560 7 Pin
Finishing Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
Color Black
Toolbox Full A Frame mounted with solid bottom and cover
Load Securement 7 pair of D-rings: 1 pr mian deck, evenly spaced, 1 pr on top of main beam at headboard
Fenders 3/16 in. deck plate

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.