

Hale Trailer Brake & Wheel 001029



20ART

20 Ton Tandem Air Tilt/Air Ramp

Tags

Base Weight: 11,020

TRAILER

Overall Length 34 ft. 6 in.
Overall Width 102 in.

Weight lbs +/- 2% 11136, including options

A-Frame 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam Hitch 3 in. pintle eye, adjustable 5 position 17 in. to 28 in.

DECK

Deck Length 21 ft. Loaded Deck Height 34 in.

Main FrameHi-Tensile Wide Flange 14 in. @ 22Cross MembersHi-Tensile 6 in. Channel @ 8.2

Side Rail Hi-Tensile 8 in. Channel @ 11.5 open on inside

Air Tilt Deck 2 Air Bags

Floor 1 3/8 in. x 7 in. Keruing Shiplapped

Landing Gear Dual 2 Speed

SUSPENSION/AXLES

Axles 25,000 lbs Capacity 77.5 in. Track 3/4 in. wall

Spread 49 in.

SuspensionHutch 9700 spring rideBrakesQuick Change 12 1/4 in. x 7 in.

Brake Chamber #3030, All Axles

Air Brake System 2S/1M
Bearings Oil Bath
Slack Adjusters Automatic

Hubs & Drums8 Stud Unimount C / W Cast DrumsTiresTire Upgrade to 235/75R17.5

Wheels 6.75 x 17.5 Steel Disc - Painted White

BEAVERTAIL

Length 6 ft. @ 6 degree slope, Planked in

RAMPS

Length 38 in. x 76 in. Air Operated Planked

GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue

Lights LED CMVSS 108 / FMVSS 108

Front Connector SAE J560 7 Pin

Finishing Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked

Color Black

Toolbox Full A Frame mounted with solid bottom and cover

Load Securement 7 pair of D-rings: 1 pr main deck, evenly spaced, 1 pr on top of main beam at

headboard

Fenders 3/16 in. deck plate

DISCLAIMER