



# Hale Trailer Brake & Wheel

## 001033



### 20NTT

#### 20 Ton Tandem Non Tilt

#### Tags

**Base Weight:** 7,960

#### TRAILER

**Overall Length** \*NPO\*: 34 ft. 8 in.  
**Overall Width** 102 in.  
**Weight lbs +/- 2%** 9056, including options  
**A-Frame** 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam  
**Hitch** 3 in. pintle eye, adjustable 5 position 23 1/2 in. to 32 1/2 in.

#### DECK

**Deck Length** 21 ft.  
**Loaded Deck Height** 34 in.  
**Main Frame** Hi-Tensile Wide Flange 14 in. @ 22  
**Cross Members** Hi-Tensile 5 in. Channel @ 6.7  
**Side Rail** Hi-Tensile 7 in. Channel @ 9.8 open on inside  
**Floor** 1 3/8 in. x 7 in. Keruing Shiplapped  
**Landing Gear** Dual 2 Speed

#### SUSPENSION/AXLES

**Axles** 25,000 lbs Capacity 77.5 in. Track 3/4 in. wall  
**Spread** 49 in.  
**Suspension** Hutch 9700 spring ride  
**Brakes** Quick Change 12 1/4 in. x 7 in.  
**Brake Chamber** #3030, All Axles  
**Air Brake System** 2S/1M  
**Bearings** Oil Bath  
**Slack Adjusters** Automatic  
**Hubs & Drums** 8 Stud Unimount C / W Cast Drums  
**Tires** 235/75R17.5  
**Wheels** 6.75 x 17.5 Steel Disc - Painted White

#### BEAVERTAIL

**Length** \*NPO\*: 6 ft. Beavertail, planked

#### RAMPS

**Length** \* 38 in. x 76 in. Wood Filled Air Operated Ramp

#### GENERAL SPECIFICATIONS

**Electrical System** Modular, Vapor Proof GROTE Ultra Blue  
**Lights** LED CMVSS 108 / FMVSS 108  
**Front Connector** SAE J560 7 Pin  
**Finishing** Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked  
**Color** Black  
**Load Securement** 7 pair of D-rings: 2 pr main deck, evenly spaced, 1 pr at headboard on main frame  
**Toolbox** Standard Mesh with, With Frame Mounted Deck Plate Cover  
**Fenders** 3/16 in. deck plate

**GVWR Rating is based on standard configuration and a 15% Tongue weight distribution**

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.