



Hale Trailer Brake & Wheel

001095



| 25NTT | | | | |
|---|--------------------|--|---|--|
| 25 Ton Tridem Non Tilt | | | | |
| Tags | | | | |
| | | Base Weight: | 11,360 | |
| TRAILER | Overall Length | *NPO*: 37 ft. 7 in. | | |
| | Overall Width | 102 in. | | |
| | Weight lbs +/- 2% | 12552, including options | | |
| | A-Frame | 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam | | |
| | Hitch | 3 in. pintle eye, adjustable 5 position 23 1/2 in. to 32 1/2 in. | | |
| DECK | Deck Length | 24 ft. | | |
| | Loaded Deck Height | 34 in. | | |
| | Main Frame | Hi-Tensile Wide Flange 14 in. @ 22 | | |
| | Cross Members | Hi-Tensile 6 in. Channel @ 8.2 | | |
| | Side Rail | Hi-Tensile 8 in. Channel @ 11.5 open on inside | | |
| | Floor | 1 3/8 in. x 7 in. Keruing Shiplapped | | |
| | Landing Gear | Dual 2 Speed | | |
| SUSPENSION/AXLES | Axles | 25,000 lbs Capacity 77.5 in. Track 3/4 in. wall ,1 Lift Axle with Control Box | | |
| | Spread | 49 in. | | |
| | Suspension | Hutch 9700 spring ride., 1 Ridewell RAR 240 Underslung Air ride 25,000lbs. (includes air gauge and dump valve) | | |
| | Brakes | Quick Change 12 1/4 in. x 7 in. | | |
| | Brake Chamber | #3030, All Axles | | |
| | Air Brake System | 2S/1M | | |
| | Bearings | Oil Bath | | |
| | Slack Adjusters | Automatic | | |
| | Hubs & Drums | 8 Stud Unimount C / W Cast Drums | | |
| | Tires | 215/75R17.5 | | |
| | Wheels | 6.75 x 17.5 Steel Disc - Painted White | | |
| | BEAVERTAIL | Length | *NPO*: 6 ft. Beavertail - Planked In | |
| | RAMPS | Length | * 38 in. x 76 in. Wood Filled Air Operated Ramp | |
| GENERAL SPECIFICATIONS | Electrical System | Modular, Vapor Proof GROTE Ultra Blue | | |
| | Lights | LED CMVSS 108 / FMVSS 108 | | |
| | Front Connector | SAE J560 7 Pin | | |
| | Finishing | Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked | | |
| | Color | Black | | |
| | Toolbox | Standard Mesh with , With Frame Mounted Deck Plate Cover | | |
| | Load Securement | 7 pair of D-rings: 1 pr at at top of main beam at headboard | | |
| | Fenders | 3/16 in. deck plate | | |
| GVWR Rating is based on standard configuration and a 15% Tongue weight distribution | | | | |
| DISCLAIMER | | | | |

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.