

HALE TRAILER BRAKE & WHEEL, INC.

presents

BWS

EZ-2-LOAD
TRAILERS

2013

1257 - 1260

TRAILER

Overall Length: 51'
Overall Width: 102"
Weight lbs +/-2%: 18,800

GOOSENECK

Coupler: Weld in king pin
Coupler Plate: 5/16" Hi-Tensile, 48" height
Coupler Location: 13"
Length: 9' 10"
Stinger Arm: Dual Air Cell, Adjustable Foot
Crossmembers: Hi-tensile 3" Jr. I-beam @ 16" O/C
Swing Clearance: 79"
Floor: 1 1/8" Shiplapped Softwood
Chain Rack: Located on back of gooseneck

DECK

Deck Length: 32' 3"
Loaded Deck Height: 20" loaded, adjustable +/-2"
Ground Clearance: 6" loaded, adjustable +/-2"
Main Frame: Fabricated 3/4" x 5" top and bottom flanges 100 KSI - 4 x 3/4 reinforced
Crossmembers: Hi-tensile 8" x 6" Jr. I-beam @ 12 O/C
Side Rail: Fabricated channel 100 KSI
Rub Rail: 5/16" x 2 1/2" steel, rear only
Web: 1/4" Hi-tensile
Floor: 1 1/8" Shiplapped Apitong/Keruing Outside on main deck, 1 1/8" Shiplapped softwood between beams, 10 gauge formed deck plate over wheels
Landing Gear: Air
Outriggers: Aluminum pullout style - rated @ 8500# per

Disclaimer

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are representative of the subject equipment, but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

SUSPENSION/AXLES

Axles:	25,000# large inner/outer oil bath bearings $\frac{3}{4}$ " wall
Spread:	49"
Suspension:	Ridewell RAR 240, 1 wishbone, 1 underslung air ride 25,000#, adjustable ride height +/-2". Includes air gauge and dump valve
Brakes:	16 $\frac{1}{2}$ " x 7", includes dust shields
Brake Chamber:	#3030, all axles
Air Brake System:	2S/1M
Slack Adjusters:	Automatic
Camshafts:	28 Spline enclosed
Hubs & Drums:	10-stud, hub piloted, long stud c/w cast drums
Tires:	255/70R 22.5
Wheels:	8.25 x 22.5 steel disc, painted white

RAMPS

Entry Ramp:	Extended – located at front of trailer
Pullout Access Ramp:	Included

GENERAL SPECIFICATIONS

Electrical System:	Modular, Vapor Proof Grote Ultra Blue
Front Connector:	SAE J560 7-pin
Rear Connector:	7-pin @ rear and 4-pin for future strobe
Lights:	LED CMVSS 108/FMVSS 108
Flip Axle Ready:	Emergency and service line, capped
Finishing/Color:	Preparation by steel shot blast, commercial/industrial topcoat, oven baked, BLACK

Disclaimer

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are representative of the subject equipment, but may not be identical. Equipment availability, prices and specifications are subject to change without notice.