



Hale Trailer Brake & Wheel  
001343



**20ART**

**20 Ton Tandem Air Tilt/Air Ramp**

**Tags**

**TRAILER**

|                          |  |
|--------------------------|--|
| <b>Overall Length</b>    | 34 ft. 6 in.   |
| <b>Overall Width</b>     | 102 in.  |
| <b>Weight lbs +/- 2%</b> | 11029  |
| <b>A-Frame</b>           | 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam     |
| <b>Hitch</b>             | 3 in. pintle eye, adjustable 5 position 17 in. to 28 in. |

**DECK**

|                           |  |
|---------------------------|--|
| <b>Deck Length</b>        | 21 ft.   |
| <b>Loaded Deck Height</b> | 34 in.   |
| <b>Main Frame</b>         | Hi-Tensile Wide Flange 14 in. @ 22             |
| <b>Cross Members</b>      | Hi-Tensile 6 in. Channel @ 8.2                 |
| <b>Side Rail</b>          | Hi-Tensile 8 in. Channel @ 11.5 open on inside |
| <b>Air Tilt Deck</b>      | 2 Air Bags                                     |
| <b>Floor</b>              | 1 3/8 in. x 7 in. Keruing Shiplapped           |
| <b>Landing Gear</b>       | Dual 2 Speed                                   |

**SUSPENSION/AXLES**

|                         |   |
|-------------------------|---|
| <b>Axles</b>            | 25,000 lbs Capacity 77.5 in. Track 3/4 in. wall |
| <b>Spread</b>           | 49 in.  |
| <b>Suspension</b>       | Hutch 9700 spring ride                          |
| <b>Brakes</b>           | Quick Change 12 1/4 in. x 7 in.                 |
| <b>Brake Chamber</b>    | #3030, All Axles                                |
| <b>Air Brake System</b> | 2S/1M   |
| <b>Bearings</b>         | Oil Bath  |
| <b>Slack Adjusters</b>  | Automatic                                       |
| <b>Hubs &amp; Drums</b> | 8 Stud Unimount C / W Cast Drums                |
| <b>Tires</b>            | 215/75R17.5                                     |
| <b>Wheels</b>           | 6.75 x 17.5 Steel Disc - Painted White          |

**BEAVERTAIL**

|               |                                    |
|---------------|------------------------------------|
| <b>Length</b> | 6 ft. @ 6 degree slope, Planked in |
|---------------|------------------------------------|

**RAMPS**

|               |                                      |
|---------------|--------------------------------------|
| <b>Length</b> | 38 in. x 76 in. Air Operated Planked |
|---------------|--------------------------------------|

**GENERAL SPECIFICATIONS**

|                          |  |
|--------------------------|--|
| <b>Electrical System</b> | Modular, Vapor Proof GROTE Ultra Blue  |
| <b>Lights</b>            | LED CMVSS 108 / FMVSS 108  |
| <b>Front Connector</b>   | SAE J560 7 Pin   |
| <b>Finishing</b>         | Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked |
| <b>Color</b>             | Black  |
| <b>Toolbox</b>           | Full A Frame mounted with solid bottom and cover                             |
| <b>Load Securement</b>   | 6 pair of D-rings: on top of mani beam at headboard                          |

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.