



Hale Trailer Brake & Wheel

001517



20ART		
20 Ton Tandem Air Tilt/Air Ramp		
Tags		
TRAILER		
Overall Length	34 ft. 6 in.	
Overall Width	102 in.	
Weight lbs +/- 2%	11029	
A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam	
Hitch	3 in. pintle eye, adjustable 5 position 17 in. to 28 in.	
DECK		
Deck Length	21 ft.	
Loaded Deck Height	34 in.	
Main Frame	Hi-Tensile Wide Flange 14 in. @ 22	
Cross Members	Hi-Tensile 6 in. Channel @ 8.2	
Side Rail	Hi-Tensile 8 in. Channel @ 11.5 open on inside	
Air Tilt Deck	2 Air Bags	
Floor	1 3/8 in. x 7 in. Keruing Shiplapped	
Landing Gear	Dual 2 Speed	
SUSPENSION/AXLES		
Axles	25,000 lbs Capacity 77.5 in. Track 3/4 in. wall	
Spread	49 in.	
Suspension	Hutch 9700 spring ride	
Brakes	Quick Change 12 1/4 in. x 7 in.	
Brake Chamber	#3030, All Axles	
Air Brake System	2S/1M	
Bearings	Oil Bath	
Slack Adjusters	Automatic	
Hubs & Drums	8 Stud Unimount C / W Cast Drums	
Tires	215/75R17.5	
Wheels	6.75 x 17.5 Steel Disc - Painted White	
BEAVERTAIL		
Length	6 ft. @ 6 degree slope, Planked in	
RAMPS		
Length	38 in. x 76 in. Air Operated Planked	
GENERAL SPECIFICATIONS		
Electrical System	Modular, Vapor Proof GROTE Ultra Blue	
Lights	LED CMVSS 108 / FMVSS 108	
Front Connector	SAE J560 7 Pin	
Finishing	Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked	
Color	Black	
Toolbox	Full A Frame mounted with solid bottom and cover	
Load Securement	6 pair of D-rings: 5 pair on side rail, 1 pair on top of main beam at headboard	
Fenders	3/16 in. deck plate	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.