



Hale Trailer Brake & Wheel 005616

Talbert Manufacturing, Inc.

Model: 28'-0" Beam deck assembly

Capacity in tons: 65

1. GOOSENECK

- 1 Electrical receptacle

Seven pin connector

2. DECK

Deck section design

Beam

Deck section length

28'-0" (27'-6" clear)

Deck section width

48" Out to out main beams

Loaded road clearance

6"

- 1 Loaded deck height

24" main beams

Flooring

None

- 1 Mainbeams

18" T-1A

Gooseneck/deck connection

Pin and plate with remote lock

- 1 Deck/rear bridge connection

Vertical pin & plate (flush connection)

Outriggers

None

- 1 Reinforced top flange of sidemember

Full length with chain slots

- 1 Additional deck specifications

Recess last 4 cross members 10" below main beams

Slope front of deck top down

Yes

- 1 Expanded metal

Between main beams 1st deck section at front and 2nd to last deck section at rear

4. GENERAL

- 1 Lights and wiring

12 volt system with the following

All lights to be LED including mid-turn, excluding license plate light

3 lights each side of deck including mid-turn

Paint

Valspar standard Talbert black, R-Cure 800 series paint

- 1 Lash rings

24 total -

8 each side of deck (straight style), 16 total

2 each side between deck main beams in the first two deck sections and 2nd & 3rd from last deck sections (bent style), 8 total

- 1 Estimated empty weight

11,380#

- 1 Compatibility

With future 10'-0" deck insert, gooseneck extension, axle attachments and E2

- 1 Design notes

1) - 65 Ton capacity in a 14'-0" two point rigid load base as a 3+2 spread axle trailer with 28'-0" of deck

2) - 65 Ton capacity in a 30'-0" two point rigid load base as a 3+2 spread axle trailer with 38'-0" of deck

3) - 70 Ton capacity in a 15'-0" two point rigid load base as a 4 axle trailer with 28'-0" of deck

Additional general specifications

None

- 1 Change order notes

Changed to 65 ton capacity - build like A/N 5579

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.