

Hale Trailer Brake & Wheel 010109



Trailer Model: KSHRG Lite: 3 Axle 45T 51 foot Model

KSHRG Lite: 3 Axle 45T 51 foot Model Standard Equipment

Net Capacity: 45 tons concentrated in 16 feet

Nominal: 51 feet 10 in OAL 8 feet 6 inches Wide

GOOSENECK:

Hydraulic Detachable Gooseneck 5 Position Adjustable Neck 50" Loaded 5th Wheel Height, 15" Setting, 2" King pin Narrow neck, Chain storage rack under gooseneck

102" Swing Radius

PTO powered: two main & one lift arm cylinders

DECK:

Nominal Deck Length: 25.5 feet

Loaded Deck Height: 23 in 5 in Loaded Ground Clearance
4 Beam design - 130,000 psi yield flanges & 100,000 web minimum

Fabricated I Main beams with lightening holes I-Beam Cross members on (approx.) 24" Centers 3 recessed cross members in the rear deck area

2" Nominal Apitong Decking - 2 board outside only, Center Open D Rings: 8 Pairs - 6 on side rail, 1 on neck & 1 on rear deck Outriggers: 12 Pair Swing out + 1 Pair Heavy duty hook on at front

Front tapered deck - approx. 7" drop to ground Bridge to rear deck is equipped with half ramp

SPAN: 43 feet (king pin to middle of mid axle)

REAR SECTION:

V style boom trough

Three Axles, 5" round, 5/8" wall 25000# nominal capacity Suspension: Ridewell or Equivalent air ride with Oil Seals 60 in axle spacing, Open wheel wells & load bearing rear bolsters Axle chains with Air bag cut off valves on Front Axle & Rear

Auto Slack Adjusters ABS: 2S1M

16-1/2in x7in Air Parking Brake on 2nd Axles
Hub: 10 Stud, Hub Piloted, Long studs, Cast Drums
275/70R22.5 16-PR Radial tires on Steel Wheels

Air Ride Suspension With 5 Position Ride Height & dump switch

GENERAL:

12V System with 7 way, Modular Harness, LED Sealed Beam Lights

Strobe light package with toggle switch on rear Epoxy Primer & Black Polyurethane Paint

Flag Holders - 2 Pairs - front deck and rear of trailer

Mid-Turn Signal/Clearance Light

Tool Tray: 2' expanded metal at front of deck (approx.)

Red & White Conspicuity tape KS Mud Flaps