

X-L SPECIALIZED

Specifications

15925

Detachable Double Drop Ext – Hydraulic Neck

Overall Length: 53'

Model Year 2016

Overall Width: 102"

Model: XL130HDE

Dist: 130,000#

Concentrated: 110,000# in 10' closed

GOOSENECK

Length:	12'5" narrow gooseneck
King Pin Setting:	16"
Swing Clearance:	105"
5 th Wheel Height:	52" w/7 variable ride height positions
Hydraulics:	Pony Motor
Flip Neck:	Frame reinforcement, air, electric and brackets for 84" flip neck ext. 84" flip neck extension

MAIN DECK

Length:	31'1"/opening to 54'5"
Loaded Deck Height:	24" w/6" ground clearance
Decking:	1 1/8" apitong decking, flush, center covered
Crossmember:	6" Jr I-beam on 12" alternating centers
Side Beams:	Fab I-Beam
D-Rings:	10 bent D-rings per side total of 20 – stagger between chain drops
Outriggers:	Removable swing out outriggers – 24" O/C
Chain drops:	(10) chain drops per side – outside beams only – stagger between D-rings

REAR DECK

Length:	9'6"
Loaded Deck Height:	36"
Axles:	(2) 25,000 nominal, 77 1/2" Tracking
Suspension:	Hend-Turner/25,000 Air
Axle Spacing:	60"
ABS:	N/A spring brakes on both axles
Tires:	Michelin 245/70R/17.5
Wheels:	6.75 x 17.5 Steel Inside, Aluminum Polished Outside Disc Wheels
Brakes:	12 1/4" x 7 1/2"
Drums:	Hub Pilot / Outboard Drums
Electrical:	12-Volt Sealed Grote System w/3-Tail Light Aluminum Package
Decking:	1 1/8" Apitong decking flush, covered wheels with open boom trough
D-rings:	2 bent D-rings in tail channel 2 pair of pan style D-rings – one in each corner

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

ADDITIONAL

(9) total clearance lights per side – LED

Paint:

BLACK Urethane w/2-part Epoxy Primer

1 pair of flag holders in rear

Raise & lower valve and liquid filled air gauge in alum. box between axles on driverside (see drawing)

31” front flip ramps

Frame reinforcement, air, brackets, electrical for two axle power booster (3+2)

4” amber strobe light to be used as 3rd tail light

LED lighting – standard

Detachable wheel area with vertical pins

PSI tire inflation system

Liquid filled air gauge

Dust shields

(3) total mid turn lights per side

Manual ride height control

Extension stops 24” O/C

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.