

HALE

TRAILER

BRAKE & WHEEL



A015937-A015940
VIN: A000394-A000400

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

20NTT 20 Ton Tandem Non Tilt Tags

Base Weight: 7,960

TRAILER

Overall Length	34 ft. 8 in.
Overall Width	102 in.
Weight lbs +/- 2%	8630, including options
A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
Hitch	3 in. pintle eye, adjustable 5 position 23 1/2 in. to 32 1/2 in.

DECK

Deck Length	21 ft.
Loaded Deck Height	34 in.
Main Frame	Hi-Tensile Wide Flange 14 in. @ 22
Cross Members	Hi-Tensile 5 in. Channel @ 6.7
Side Rail	Hi-Tensile 7 in. Channel @ 9.8 open on inside
Floor	1 3/8 in. x 7 in. Keruing Shiplapped
Landing Gear	*NPO*: Galvanized Landing Gear
Step	Bolt on, Located on Front Corner of deck, Driver side

SUSPENSION/AXLES

Axles	25,000 lbs Capacity 77.5 in. Track
Spread	49 in.
Suspension	Heavy Duty spring ride
Alum Air Tank	*NPO*: Drain plug with cable
Brakes	Quick Change 12 1/4 in. x 7 in.
Brake Chamber	#3030, All Axles
Air Brake System	2S/1M
Air Tank(s)	Aluminum
Bearings	Oil Bath
Slack Adjusters	Automatic
Hubs & Drums	8 Stud Unimount C / W Cast Drums
Tires	235/75R17.5 16 ply
Wheels	6.75 x 17.5 Steel Disc - Painted White

BEAVERTAIL

Length	6 ft. Beavertail, Planked
--------	---------------------------

RAMPS

Length	20 in. x 60 in. Spring assist, self cleaning, adjustable total width 99 in. max./ 68 in. min.
--------	---

GENERAL SPECIFICATIONS

Electrical System	Modular, Vapor Proof GROTE Ultra Blue
Lights	LED CMVSS 108 / FMVSS 108
Front Connector	SAE J560 7 Pin
Color	Galvanized
Mudflaps	1 set of BWS at rear
Toolbox	Full A Frame mounted with solid bottom and aluminum cover

20NTT 20 Ton Tandem Non Tilt Tags

Base Weight: 7,960

GENERAL SPECIFICATIONS

Load Securement 7 pair of D-rings: 5 pr main deck, evenly spaced; 1 pr on B/T, 1 pr on main beam at headboard

Fenders 3/16 in. deck plate

GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.