



Hale Trailer Brake & Wheel 016678

components description

CAPACITY GVWR 70,000 lbs / 50,000 lbs. in 16'
OVERALL LENGTH 44'
OVERALL WIDTH 8' 6"
DECK LENGTH 25' 9"
DECK HEIGHT 33" - Loaded
DECK FLOORING 1 3/4" - Apitong - covering entire deck
MAINBEAMS Fabricated Mainbeams
CROSSMEMBERS 6" I-Beams - Pierced Through Mainbeams
SIDE RAILS 8" I-Beam
GOOSENECK Smooth Neck - 60" Steel Check Plate Ramp
KING PIN SETTING 18"
KING PIN SWING RADIUS 84"
KING PIN HEIGHT 48"
DOVETAIL 5' Self Cleaning outside w/Open Center
WHEEL WELL Covered w/ Steel Check Plate
LOADING RAMP Spring Assisted - 24" X 60" - Self Cleaning
LANDING GEAR 50,000 lbs Capacity
D RING 10 Total - 8 on Bed - 2 on Neck
AXLE (2) 22,500 lb. Capacity - Brakes 12 1/4" x 7 1/2" - Auto Slack, ABS-2s/1M
SUSPENSION Hutch - 3 Leaf/Heavy Duty Springs
WHEELS Disc - Hub Piloted
TIRES 215/75R17.5 Radials
TOOLBOX In Neck
WIRING Sealed Wiring Harness
LIGHTS LED Pkg - Sealed Lights Rubber Mounted
FINISH Sand Blasted and Painted with Two Part Acrylic Polyurethane
COLOR Haulass High Gloss Black

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.