



Hale Trailer Brake & Wheel
019930

X-L SPECIALIZED TRAILERS, INC.

OAL: 53'
OAW: 102"

MODEL: XL120SDE DIST: 120000# CONC. 100,000# IN 10' CLOSED

WEIGHT +/-3%= 22,900

GOOSENECK-

LENGTH: 11' 6" NARROW GOOSENECK
 KING PIN SETTING: 16"
 SWING CLEARANCE: 102"
 5TH WHEEL HEIGHT: 52"
 DECKING: NONE
 STAKE POCKETS: NONE
 LANDING GEAR: 2 SPEED, HANDLE ON ROADSIDE
 FLIP NECK: FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR 66" FLIP NECK EXTENSION
 66" FLIP NECK

MAIN DECK-

LENGTH: 41' 6" EXTENDING TO 64' 4"
 LOADED DECK HGT: 33" OPEN WHEELS
 DECKING: 1 1/8" APITONG DECKING FLUSH
 CROSSMEMBER: 4" JR. I-BEAM ON 12" CTRS.
 SIDE BEAMS: 6" MILL CHANNEL
 STAKE POCKETS: 24" O/C, 5/16" X 2" RUB RAIL W/ SINGLE PIPE SPOOLS
 D-RINGS: 7 PAIR OF PAN STYLE D-RINGS ON MAIN DECK--EVENLY SPACED
 7 PAIR OF FLAT D-RINGS AT BOTTOM OF KNEE BRACES

REAR DECK:

LENGTH: 33"
 LOADED DECK HEIGHT: 33"
 AXLES: (3) 25,000 NOMINAL, 77 1/2" TRACKING LIMIT CHAINS ON ALL 3 AXLES
 SUSPENSION: HEND-TURNER/25,000 AIR
 AXLE SPACING: 60"
 ABS: N/A SPRING BRAKES ON 1 AXLE
 TIRES: MICHELIN 245/70R/17.5
 WHEELS: 6.75 X 17.5 STEEL INSIDE, ALUMINUM POLISHED OUT DISC WHEELS
 BRAKES: 12 1/4" X 7 1/2"
 DRUMS: HUB PILOT/ OUTBOARD DRUMS
 ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAILLIGHT ALUMINUM PACKAGE
 MANUAL RIDE HEIGHT CONTROL
 1 PAIR OF BENT D-RINGS IN TAIL CHANNEL

ADDITIONAL:

PAINT: BLACK URETHANE WITH 2 PART EPOXY PRIMER
 1 EXTRA LIGHT PER SIDE AT START OF MAIN DECK
 FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR 2 AXLE POWER BOOSTER
 4" AMBER STROBE LIGHT TO BE USED AS 3RD TAIL LIGHT
 DUST SHIELDS
 (1) 4 WAY PLUG IN EACH CORNER OF MAIN DECK
 PSI TIRE INFLATION SYSTEM ON ALL 3 AXLES
 LIQUID FILLED AIR GAUGE AND RAISE AND LOWER VALVE MOUNTED IN BOLSTER
 (1) 4 WAY PLUG IN REAR BOLSTER - BOTH SIDES

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.