



Hale Trailer Brake & Wheel

019954

X-L SPECIALIZED TRAILERS, INC.

OAL: 53'
OAW: 102"

MODEL: XL100SDE DIST: 100000# CONC. 80,000# IN 10' CLOSED
WEIGHT +/-3%=

GOOSENECK-

LENGTH: 10'
KING PIN SETTING: 16"
SWING CLEARANCE: 84"
5TH WHEEL HEIGHT: 49"
DECKING: 1 1/8" APITONG DECKING FLUSH
STAKE POCKETS: 24" O/C WITH 5/16" X 2" RUB RAIL W/ SINGLE PIPE SPOOLS
LANDING GEAR: 2 SPEED W/ HANDLE DRIVER SIDE
FLIP NECK: 36" FLIP NECK EXTENSION
FLIP NECK: FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR 36" FLIP NECK

MAIN DECK-

LENGTH: 43' EXTENDING TO 67' 4"
LOADED DECK HGT: 30" WITH OPEN WHEELS
DECKING: 1 1/8" APITONG DECKING FLUSH
CROSSMEMBER: 4" JR. I-BEAM ON 12" CENTERS
SIDE BEAMS: 6" MILLED SIDE RAILS
STAKE POCKETS: 24" O/C WITH 5/16" X 2" RUB RAIL W/ SINGLE PIPE SPOOLS
(3) PAIR OF PAN STYLE D-RINGS AT FRONT OF MAIN DECK ON 36" CENTERS, STARTING 1' REAR OF GOOSENECK
(3) PAIR OF PAN STYLE D-RINGS AT REAR OF MAIN DECK ON 36" CENTERS
(6) PAIR D-RINGS ON MAIN BEAM FLANGES - (3) FRONT - (3) REAR

AXLES: (3) 25,000 NOMINAL, 77 1/2" TRACKING LIMIT CHAINS ON 1ST AND 2ND AXLES
SUSPENSION: HEND-TURNER/25,000 AIR RIDE
AXLE SPACING: 60"
ABS: 4S2M SPRING BRAKES ON 2 AXLES
TIRES: MICHELIN 245/70R/17.5
WHEELS: 6.75 X 17.5 ALUMINUM POLISHED OUT STEEL IN DISC WHEELS
BRAKES: 12 1/4" X 7 1/2"
DRUMS: HUB PILOT/ OUTBOARD DRUMS
ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAILLIGHT PACKAGE
TWO D-RINGS ON EACH BOLSTER

ADDITIONAL:

PAINT: PSI TIRE INFLATION SYSTEM ON ALL AXLES
BLACK URETHANE WITH 2 PART EPOXY PRIMER
RAISE AND LOWER VALVE
LED LIGHTING - STANDARD
MANUAL RIDE HEIGHT CONTROL
4" AMBER STROBE LIGHT TO BE USED AS 3RD TAIL LIGHT
FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR SINGLE AXLE BOOSTER
LIQUID FILLED AIR GAUGE
(1) 4 WAY PLUG AT REAR OF TRAILER
CHAIN UP AXLE ON 3RD AXLE WITH DUMP VALVE - DUAL RIDE HEIGHTS

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.