

## Hale Trailer Brake & Wheel 019970

## X-L SPECIALIZED TRAILERS, INC. OAL: 48' OAW: 102"

MODEL: XL 70MDE DIST: 70,000# CONC. 50,000# IN 10' CLOSED WEIGHT +/-3%

GOOSENECK-

 LENGTH:
 10'

 KING PIN SETTING:
 16"

 SWING CLEARANCE:
 84"

 5TH WHEEL HEIGHT:
 48"

TRIPLE DONUTS FOR HEIGHTS AT 46", 48" AND 50"

DECKING: 1 1/8" APITONG DECKING, FLUSH

**D-RINGS:** 2 PAIR OF PAN STYLE D-RINGS (ONE EACH CORNER)

D-RINGS: 2 BENT D-RINGS PER SIDE MUD FLAPS: ALUMINUM MUD FLAPS

TOOLBOX: TOOLBOX IN REAR OF GOOSENECK WITH ALUMINUM COVER

LIGHT IN TOOLBOX WITH CHAIN RACK

FLIP NECK: FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR 36" FLIP NECK EXT.

TO FIT FLIP NECKS FROM HALES STOCK 80MFG TRAILERS

**MAIN DECK-**

LENGTH: 29' EXTENDING TO 50' 4"

LOADED DECK HGT: 16" W/ 4" GROUND CLEARANCE

DECKING: 1 1/8" APITONG DECKING FLUSH

CROSSMEMBER: 4" JR. I-BEAM ON 12" ALTERNATING CENTERS

SIDE BEAMS: FABRICATED OUTSIDE RAIL

D-RINGS: 8 BENT D-RINGS PER SIDE - 16 TOTAL
OUTRIGGERS: SWINGOUT OUTRIGGERS ON 24" CENTERS

**REAR DECK-**

LENGTH: 9'
LOADED DECK HGT: 36"

**AXLES:** (2) 25,000 NOMINAL, 77 1/2" TRACKING

SUSPENSION: HEND-TURNER/25,000 AIR

AXLE SPACING: 54

ABS: 4S2M WITH SPRING BRAKES ON 2 AXLES

TIRES: 245 / 70R / 17.5 MICHELIN

WHEELS: 6.75 X 17.5 STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC WHEELS

BRAKES: 12 1/4" X 7 1/2"

**DRUMS**: HUB PILOT/OUTBOARD DRUMS

**ELECTRICAL**: 12V SEALED GROTE SYSTEM WITH 3 TAILLIGHT ALUMINUM PACKAGE

4" AMBER STROBE WITH SWITCH TO MAKE 3 STT

**DECKING:** 1 1/8" APITONG DECKING, FLUSH, COVERED WHEELS

STAKE POCKETS: 2 STAKE POCKETS IN TAIL CHANNEL 2 PAIR OF PAN STYLE D-RINGS (ONE EACH CORNER)

ADDITIONAL:

PAINT: BLACK

ONE PAIR OF FLAG HOLDERS ON FRONT & REAR

FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR FLIP AXLE

RAISE AND LOWER VALVE MANUAL RIDE HEIGHT CONTROL EXTENSION STOPS ON 24" CENTERS

66" WIDE BUMPER

PSI TIRE INFLATION SYSTEM