



# Hale Trailer Brake & Wheel

019977

OAL: 53'  
OAW: 102"

MODEL: XL120SDE DIST: 120000# CONC. 100,000# IN 10' CLOSED

**X-L SPECIALIZED TRAILERS, INC.** WEIGHT +/-3%= 22,900

**GOOSENECK-**

LENGTH: 11' 6" NARROW GOOSENECK  
 KING PIN SETTING: 16"  
 SWING CLEARANCE: 102"  
 5TH WHEEL HEIGHT: 52"  
 DECKING: NONE  
 STAKE POCKETS: NONE  
 LANDING GEAR: 2 SPEED, HANDLE ON ROADSIDE  
 FLIP NECK: FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR 66" FLIP NECK EXTENSION  
 66" FLIP NECK

**MAIN DECK-**

LENGTH: 41' 6" EXTENDING TO 64' 4"  
 LOADED DECK HGT: 33" OPEN WHEELS  
 DECKING: 1 1/8" APITONG DECKING FLUSH  
 CROSSMEMBER: 4" JR. I-BEAM ON 12" CTRS.  
 SIDE BEAMS: 6" MILL CHANNEL  
 STAKE POCKETS: 24" O/C, 5/16" X 2" RUB RAIL W/ SINGLE PIPE SPOOLS  
 D-RINGS: 7 PAIR OF PAN STYLE D-RINGS ON MAIN DECK--EVENLY SPACED  
 7 PAIR OF FLAT D-RINGS AT BOTTOM OF KNEE BRACES

**REAR DECK:**

LENGTH: 33"  
 LOADED DECK HEIGHT: 33"  
 AXLES: ( 3 ) 25,000 NOMINAL, 77 1/2" TRACKING LIMIT CHAINS ON ALL 3 AXLES  
 SUSPENSION: HEND-TURNER/25,000 AIR  
 AXLE SPACING: 60"  
 ABS: N/A SPRING BRAKES ON 1 AXLE  
 TIRES: MICHELIN 245/70R/17.5  
 WHEELS: 6.75 X 17.5 STEEL INSIDE, ALUMINUM POLISHED OUT DISC WHEELS  
 BRAKES: 12 1/4" X 7 1/2"  
 DRUMS: HUB PILOT/ OUTBOARD DRUMS  
 ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAILLIGHT ALUMINUM PACKAGE  
 MANUAL RIDE HEIGHT CONTROL  
 1 PAIR OF BENT D-RINGS IN TAIL CHANNEL

**ADDITIONAL:**

PAINT: BLACK URETHANE WITH 2 PART EPOXY PRIMER  
 1 EXTRA LIGHT PER SIDE AT START OF MAIN DECK  
 FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR 2 AXLE POWER BOOSTER  
 4" AMBER STROBE LIGHT TO BE USED AS 3RD TAIL LIGHT  
 DUST SHIELDS  
 ( 1 ) 4 WAY PLUG IN EACH CORNER OF MAIN DECK  
 PSI TIRE INFLATION SYSTEM ON ALL 3 AXLES  
 LIQUID FILLED AIR GAUGE AND RAISE AND LOWER VALVE MOUNTED IN BOLSTER  
 ( 1 ) 4 WAY PLUG IN REAR BOLSTER - BOTH SIDES

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.