

## Hale Trailer Brake & Wheel 020187

## X-L SPECIALIZED TRAILERS, INC. OAL: 51'

OAW: 102"

**WEIGHT +/-3%** 

CONC. 120,000# IN 16' (CENTERED)

CONC. 110,000# IN 10'

MODEL: XL 120 HDGS **DIST:** 120,000#

**GOOSENECK-**

LENGTH: 13' SCRAPER RELIEF STYLE NECK

KING PIN SETTING: 16" 30" SWING CLEARANCE: 110" 96"

5TH WHEEL HEIGHT: 51" W / 5 VARIABLE RIDE HEIGHT POSITIONS

FLIP NECK: FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR 36" FLIP NECK

HYDRAULICS: WET KIT

MAIN DECK-

ENGTH: 24' BEAM DECK

LOADED DECK HGT: 24" W/8" GROUND CLEARANCE

DECKING: **CENTER OPEN** CROSSMEMBER: PER ENGINEERING SIDE BEAMS: 2 BEAMS 16" OUTRIGGER: NONE

D-RINGS: 12 BENT D-RINGS PER SIDE - SET LOW

6 FLAT D-RINGS PER SIDE ON INSIDE OF MAIN DECKS - SET HIGH

REAR DECK:

CHAIN DROPS:

LENGTH: 14' WITH 32\* REAR TRANSITION

LOADED DECK HEIGHT:

AXLES: (3) 25,000 NOMINAL, 77 1/2" TRACKING SUSPENSION: HEND - TURNER / 25,000 CAPACITY / AIR

AXLE SPACING: 54 1/2"

ABS: N/A SPRING BRAKES ON 1 AXLES

TIRES: 275 / 70R / 22.5

WHEELS: 8.25 X 22.5 / STEEL INSIDE, DURABRIGHT OUTSIDE / DISC / PILOTED HUBS

BRAKES: 16 1/2" X 7"

DRUMS: HUB PILOT/OUTBOARD DRUMS

ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAIL LIGHT ALUM. PACKAGE

4" AMBER STROBE WITH SWITCH TO MAKE 3 STT

**BATTERY BACKUP** 

OPEN WHEELS BOLSTER STYLE, OPEN BOOM TROUGH DECKING:

D-RINGS: (2) FLAT D-RINGS AT REAR ON MAIN BEAMS

6 PAIR OF BENT D-RINGS IN BOOM TROUGH OF WHEEL AREA (2) CHAIN DROPS PER BOLSTER

STAKE POCKETS: (2) STAKE POCKETS AT REAR

ADDITIONAL: MANUAL RIDE HEIGHT CONTROL

PAINT: **GALVANIZE** 

FRAME REINFORCEMENT FOR TWO AXLE BOOSTER BRACKETS, AIR & ELEC.

RAISE AND LOWER VALVE LED LIGHTING - STANDARD

BUCKET WELL AT REAR OF MAIN DECK WITH PLATE ON BOTTOM WITH 4 D-RINGS

TOOLBOX AT FRONT OF MAIN DECK WITH 4 D-RINGS

LID FOR TOOBOX - TO BE GALVANIZED

2 PAIR OF FLAG HOLDERS

FRONT RAMP UPPER FLANGE REINFORCEMENT

AIR LIFT AXLE ON 3RD AXLE LIQUID FILLED AIR GAUGE

4-WAY PLUG AT REAR TO RUN BATTERY BACKUP FOR STROBE