



Hale Trailer Brake & Wheel

020399

components	description
CAPACITY	Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH	45'
OVERALL WIDTH	8' 6"
KING PIN SETTING	30" - Tapered Front
UPPER COUPLER PLATE	1/4"
UPPER COUPLER HEIGHT	48"
FRONT SKIRT	Steel
REAR SKIRT	Steel
BULKHEAD	None
MAIN FRAME	26" Fab.-PreCamb.I-Beams-(80K Pkg)
SIDE RAILS	6" - Alum- Extruded W/Double L Track
FLOOR SILLS	4" Steel I-Beam 12" O.C. HD Pkg.
COIL HAUL PACKAGE	None
FLOOR DECKING	1-1/8" HD Aluminum W/4 Nailer Boards
WINCH TRACK	Double L Aluminum- Extruded Siderail R/S Only
TIE BAR	Curb Side - Full Length - 3/8" x 2"
WINCHES	12 DOUBLE L (+)#75
STRAPS	None
SUSPENSIONS	Air Ride - Cush - CP-25K 2 Axle - Fixed
SUSPENSION LOCATION	Set 66" to CL of Rear Axle to Rear of Trailer
AXLES	(2) 25K Capacity- Type 30 Chambers- Auto Slacks
AXLE SPACING	10'2" Wide Spread
LANDING GEAR	Two Speed
LIFT AXLE	Air Lift 1 Axle Front (+195#)
DUMP VALVE	None
SCALES	None
ABS SYSTEM	ABS System 2S/1M
PARKING BRAKES	All Axles
DUST SHEILDS	None
TIRE INFLATION SYSTEM	None
TIRES	11R 22.5- DOUBLE COIN
WHEELS	Disc - Hub Piloted - 22.5 Steel
ANTI-SAIL MUD FLAPS	Behind Rear Axle
STAKE POCKETS	24" O.C. Sides & 4 Across Front
SPOOL	Triangular Shaped
RUB BAND ALUM	3/8" x 3" - Aluminum - Recessed for DOT Tape
CARGO TIE DOWN	None
TOOLBOX MATERIAL	None
TOOLBOX TYPE	None
TOOLBOX LOCATION	None
TIRE CARRIERS	None
LIGHTS	Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
CUSTOM LIGHTS	None
FORK LIFT KIT MODELS	Universal MT Lift Hauler- Moffet M55 & Princeton PB50 W/Folding Bumper(1ULH002)
FORK GUIDES	4ft Forks Non-Tubular Guides

COUNTER BALANCE	45' = 1000#
COUNTER BALANCE CLAUSE	MFG. Only Responsible For Issues With Listed Forklift Models
PAINT	Black
CUSTOM 1	None
CUSTOM 2	None
CUSTOM 3	None
CUSTOM 4	None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.