

# HALE

## TRAILER






BRAKE & WHEEL



027325  
VIN: 65146

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 \*FINANCING AVAILABLE

### Velocity 48' Sliding Spring Tandem (HCVSF12SST)

Qty.: 100	Est. Wt.: 12,071# +/- 3%
<b>Length / Width:</b> 48 feet x 102 inches	
<b>Suspension Type:</b> Sliding spring tandem	
<b>Frame Rating:</b> 80,000 lbs distributed	
<b>Flooring:</b> 1 1/8 inch wood	
<b>Crossmembers:</b> 12 inch centers - 4 inch jr. I-steel	
<b>Side Rails:</b> 6 inch structural channel @ 6.5 lbs/ft	
<b>Stake Pockets:</b> 3/16 inch steel on 24 inch centers	
<b>Rubrail:</b> 2 1/2 inch rolled formed steel	
<b>Main Beams:</b> Minimum grade 130 flanges <b>Deeper Web at Rear</b>	
<b>Kingpin:</b> 30 inches	
<b>Loaded Fifth Wheel Height:</b> 49 inches	
<b>Landing Gear:</b> OEM Standard	
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C	
<b>Bulkheads:</b> <b>Removable steel bulkhead - no turnback - 48 inches high</b>	
<b>Bulkhead Pockets:</b> 4 - F-5 DOT-type steel	
<b>Number of Axles:</b> 2	
<b>Axle Spindle:</b> Tapered	
<b>Brakes:</b> Spring brakes, auto slacks	
<b>ABS:</b> 4S/2M - no cable or tool	
<b>Axle Spread:</b> 49 inches	
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums	
<b>Wheel Ends:</b> Oil in hubs	
<b>Wheels:</b> 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD	
<b>Tires:</b> 295/75R 22.5 14PR OEM standard tires - STANDARD	
<b>Suspension Detail:</b> Hutch H-9700 3-leaf spring slider - 60 inches adjustable	
<b>Front Corners:</b> Tapered	
<b>Electrical System:</b> LED: 3 lights/side, 2 lights/side on rear- STANDARD	
<b>Paint:</b> Black urethane with Velocity decals - STANDARD	
<b>Conspicuity Tape:</b> Per NHTSA specs - installed in recess on rubrails	
<b>Bumper:</b> Weld-on type - meets underride requirements	
<b>Mudflaps:</b> 1 set Velocity	
<b>Spare Tire Carrier:</b> None standard	
<b>Winch Track:</b> Steel on road side <b>Full Length</b>	
<b>Sliding Winches:</b> 12 standard - without straps	
<b>Winch Straps:</b> None standard	
<b>Dock Bumpers:</b> 1 pair rubber on rear	
<b>Hubodometer:</b> None standard	
<b>Registration Holder:</b> <b>Install registration holder - OEM standard</b>	
<b>Tool Box:</b> None standard	
<b>VIN Plate:</b> Standard US VIN plate	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.