



Hale Trailer Brake & Wheel 028144

Trailer Model:

Kalyn Hydraulic Sliding Axle (KHSA) 3 Axle, 55 Ton, 53' Model

3 Axle, 55 Ton, 53' Model Standard Equipment

Net Capacity: 55 Tons 110,000 lbs Distributed in 53 ft, 70,000 lbs Concentrated in 10 ft

Nominal: 53 feet OAL

8 feet 6 inches Wide

GOOSENECK:

10'-8" Gooseneck Length (48' & 50') / 11'-6" (53')
48" Loaded 5th Wheel Height, 18" Kingpin Setting
86" Swing Radius (48' & 50') / 96" Swing Radius (53')
20,000# Planetary Winch With Air Clutch; 100' of 5/8" Cable
Work lights on the winch 2 Tool compartments
Wet Kit: Trailer Operation; 3/4" Hydraulic Couplings

Integrated Tool Box in Neck W/ Stainless Hinges and Alum. Door

2-Speed Landing Gear , Crank Handle Roadside

DECK:

Nominal Deck Length: 41.5 feet
Nominal Deck Width: 102 in
Loaded Deck Height: 38.5 in

5 Beam design - 100,000 psi yield flanges & 80,000 web minimum

14" tall main beams and 15" tall side rails

4" I-beam cross members on 9" Centers,1-3/8" Apitong Deck(full width)

Double Key Hole Chain Slots in Upper Flange on 36" Centers

Double Key Hole Chain Slots Along Center of Deck on 36" Centers Reinforced Rear Approach Plate with 6 Chain Slots

Cable Roller Centered at Front of Lower Deck

Dump angle 16 ° Loading angle 7 °

SUSPENSION:

25,000 lb nominal capacity with Oil seals, 5/8" wall, tapered spindles

50" axle spacing 71" track

12-1/4" x 7-1/2" Brakes ABS Module: 4S2M Auto Slack Adjusters and Spring Brakes on all Axles

6.75 x 17.5 Hub Piloted Disc Wheels

235/75 R 17.5 16PR Tires Manual Dump Valve Suspension: Ridewell or Equivalent Air ride Air Ride

Alignment Bracket for Sliding Suspension

GENERAL:

12 Volt System with 7 way Sealed Harness DOT Rubber Mounted Sealed Beam LED Lights Epoxy Primer & Black Polyurethane Paint 2 Function Wireless Remote for Winch Heavy Duty DOT Approved Bumper

Red & White Conspicuity tape

KS Mud Flaps

3 LED marker lights each side including mid turn

Strobe light with toggle switch on rear

Kalyn Hydraulic Sliding Axle (KHSA) Optional Equipment

Models 3 Axle, 55 Ton, 53' Model

Options 2nd Roller Rear of Upper Deck

6 Function Wireless Remote

Aluminum Wheels OS (Polished) all Axle

Tire Inflation

Central Lube - 24 Point Manual

Estimated Weight of the Equipment with the options : 22,235 lbs.