

HALE TRAILER BRAKE & WHEEL



029187
VIN: 85193

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

BASE MODEL: EF48 | Extendable Flatbed

components	description	
CAPACITY	Heavy Duty Package - 100,000 lbs. GVWR (80,000 in 10' Span Closed)	
OVERALL LENGTH	48' - 80'Extendable Trailer	
OVERALL WIDTH	8' 6"	
KING PIN SETTING	24"	
UPPER COUPLER PLATE	1/4"	
* * 3rd Gladhand Design to Operate Lock and Release on Locking Pins * * * * Sign stating Locking Pin Release above 3rd Gladhand * * * * Eliminate Box, Valving, and Bracket on Side of Trailer * * * * Tapered Front Plate to allow Easier Hook Up for Multiple Trucks * *		
UPPER COUPLER HEIGHT	48"	
BULKHEAD	Removable Steel - 48" - No Side Return	
* * Last Post on Headboards to Cap Off Headboards * *		
MAINFRAME	26" Fabricated - PreCambered I-Beams	
* * * 11' Front Deck and 37' Rear Deck * * *		
*****Insert 10GA." - Approx 33" Wide - Plate Under Top Flange From Flange to Flange to Allow Customer to walk from Deck to Deck When Trailer is Extended*****		
SIDE RAILS	6" - 6.5# Per Foot	
* * New Tapered Corner Design * *		
* * Pipe and Bullet Connection at Connection Points to help maintain squareness * *		
FLOOR SILLS	4" I-Beam 12" O.C. STD Pkg Capacity	
FLOOR DECKING	1-1/8" Apitong	
WINCH TRACK	Steel Slide Entire Length of Drivers Side	
WINCHES	12	
STRAPS	None	
LANDING GEAR	Two Speed	
* * Landing Gear Bracing to one Horizontal Brace from Box to Box * *		
SUSPENSIONS	Spring Ride - Fixed - Hutchens - 3 Axles (-388#)	
DUMP VALVE	None	
SCALES	None	
AXLES	(3) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - Spring Ride	
***** 5/8 Wall Axles*****		
AXLE SPACING	49"	
PARKING BRAKES	3 Axle	
DUST SHEILDS	None	
WHEELS	11R22.5	
Double Coin Tires.		
ANTI-SAIL MUD FLAPS	On Rear Skirt	
STAKE POCKETS	4" Deep - 24" O.C. & 6 Across Front, 3 Across Rear	
RUB BAND STEEL	1/4" X 2-1/2"	
PIPE SPOOLS	Double	
DOCK BUMPERS	Rubber Inboard	
TIRE CARRIERS	None	
TOOLBOXES	None	
TOOLBOX TYPE	None	
LIGHTS	Sealed Wiring Harness w/ LED Pkg	
** Wiring to be Rerouted Per Pictures of Competition (Eliminate Welded Brackets to Main Frame Bottom Flange. **		
PAINT	Black	
CUSTOM 1	None	
CUSTOM 2	None	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.