

Hale Trailer Brake & Wheel 030117

BASE MODEL: FCLH | Combo Flat Lift Hauler

BASE MODEL: FCLH	
components	description
CAPACITY	Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH	34'
OVERALL WIDTH	8' (-273#)
96" Wide Trailer.	
KING PIN SETTING	30" - Tapered Front
UPPER COUPLER PLATE	1/4"
UPPER COUPLER HEIGHT	48"
FRONT SKIRT	Steel
REAR SKIRT	Steel
BULKHEAD	None
MAIN FRAME	26" FabPreCamb.I-Beams-(80K Pkg)
SIDE RAILS	6" - Alum- Extruded W/Double L Track
FLOOR SILLS	4" Steel I-Beam 12" O.C. HD Pkg.
COIL HAUL PACKAGE	None
FLOOR DECKING	1-1/8" HD Aluminum W/4 Nailer Boards
WINCH TRACK	Double L Aluminum- Extruded Siderail R/S Only
TIE BAR	Curb Side - Full Length - 3/8" x 2"
WINCHES	12 DOUBLE L (+)#75
STRAPS	None
SUSPENSIONS	Spring Ride Hutch Slider w/H9700 2 Axle 23K
SUSPENSION LOCATION	Slider/Variable
AXLES	(2) 22.5K Capacity- Type 30 Chambers- Auto Slacks
AXLE SPACING	49" (+35#)
LANDING GEAR	Two Speed
LIFT AXLE	None
DUMP VALVE	None
SCALES	None
ABS SYSTEM	ABS System 2S/1M
PARKING BRAKES	All Axles
DUST SHEILDS	None
TIRE INFLATION SYSTEM	None
TIRES	11R 24.5- DOUBLE COIN
WHEELS	Disc - Hub Piloted - 24.5 Steel (+56#)
ANTI-SAIL MUD FLAPS	Behind Rear Axle
STAKE POCKETS	24" O.C. Sides & 4 Across Front
SPOOL	Triangular Shaped
RUB BAND ALUM	3/8" x 3" - Aluminum - Recessed for DOT Tape
CARGO TIE DOWN	None
TOOLBOX MATERIAL	None
TOOLBOX TYPE	None
TOOLBOX LOCATION	None
TIRE CARRIERS	None
LIGHTS	Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
CUSTOM LIGHTS	None
FORK LIFT KIT MODELS	Moffet Kit- No Princeton Arms(17-SUB-AB513)
FORK GUIDES	4ft Forks Non-Tubular Guides
COUNTER BALANCE	34' = 3000#
	SEMFG. Only Responsible For Issuses With Listed Forklift Models
PAINT	Black
CUSTOM 1	None
CUSTOM 2	None
CUSTOM 3	None
CUSTOM 4	None
33313W17	Itolio