

CAPACITY

Specifications

2015

Sabre5 on Road 4x2 Warehouse and Distribution Truck

Electrical: 12 Volt Negative Ground

GCVWR: Up to 81,000 lbs.

30149-30158

ENGINE:	Cummins QSBT3 6.7L 160 Horsepower 2500 RPM Turbocharged & Charge Air Cooled 3 Way shut-down low oil, PSI, High Coolant Temp, Low Coolant Level Air cleaner filter Air intake restriction gauge-Engine Mounted Bendix ADIP Air Dryer Vertical Exhaust System Exhaust Heat Shield
ELECTRICAL:	130 AMP Alternator Group, 31, 750 CCA Maintenance Free Batteries Battery disconnect Denso Starter
COOLING SYSTEM:	Silicone Coolant Hoses Coolant Recovery Bottle
EXHAUST:	Vertical w/ Heat Shield
TRANSMISSION:	Allison RDS-3000 Lever Shift Transmission Selector
STEERING:	TAS-65 Power Steering Standard Steering Column
CHASSIS:	Standard Capacity Bumper 50 Degree Taper Curb Side Deck and Bumper Cab Guards Frame Structure 116" 82" Between Cab & Center 5 th Wheel (In Up Position) and Cab Flexible Rear Fenders Tire Flaps Behind Drive Axle, w/Capacity Logo Front Tow Hook Rear Tow Hook
Options:	Two Battery, Battery Box Step Style Three Drain Pull Cord
FUEL TANK:	50 Gallon "D" Tank
AXLES:	Meritor FF-961 12,000 lb. Capacity Meritor RS24-160 7.17:1 Ratio 30,000 lb. Terminal Rating
FRONT SUSPENSION:	10L-9R Leaf
REAR SUSPENSION:	Rigid Suspension

Disclaimer

Specifications are believed to be correct but may contain errors and/or omissions. Photographs are representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

FIFTH WHEEL:	SAF Holland, FW35 - 70,000 lb. Lift Capacity 5 th Wheel Lift Height 16"
TIRES & WHEELS:	Dunlop SP160 11R 22.5 Rib Tires Standard Valve Stems, TR-572 (0°)
CAB:	66" Vista Cab
CAB ELECTRIC:	Auxiliary Power Socket, Back up alarm, keyed ignition, power terminal overhead. Power Terminal Overhead, Left Side
CAB OPTIONS:	4 point air ride cab, cab insulation, door locks, translucent sun visor, windshield wash w/electric intermittent windshield wipers, Air Horn, Dual Trumpet, volt meter, oil pressure, water temperature, fuel level, air pressure, hour meter, speedometer, odometer, high beam headlight indicator, turn signal-hazard flasher indicator, low fuel, low air and low engine oil pressure light & buzzer, 12' straight trailer air hoses, standard red & blue glad hand.
HVAC:	45,000 BTU Heater/Defroster Air Conditioning Air Conditioning Compressor
LIGHT OPTIONS:	Dome Light, Head Lights, Recessed Rear/Stop Lights & Back-up Lights- LED, Five top of cab clearance lights-LED, Amber strobe light, Worklight, One rear facing curb side platform mounted-LED, Worklight, One rear facing driver side roof mount- LED
MIRROR OPTIONS:	Heated mirrors w/right side motorized 8" Convex Mirrors
SEAT OPTIONS:	National 2000 Series Vinyl Mid-Back Driver's Seat Seat Belt-Black- Lap
PAINT:	Std. Bumper-Black, Std. Cab Paint White, Std. Wheels Painted White, Std. Steps, Grates & Handrails Paint "Safety Yellow", Std. Platform Paint White, Std. Frame Paint Black, Std. Rhino Bed Liner, Rear of Cab and Back Half of Hood ALL STEPS, HANDRAILS & GRATING SAFETY YELLOW
MANUALS:	Allison Operator Manual 906055 Allison Shift Selector & Code Manual 906054 Driver Orientation 908265 Operator Video 908255 Operator's Handbook 909108 Parts Book 906053 PTO Install & Owner's Manual

Disclaimer

Specifications are believed to be correct but may contain errors and/or omissions. Photographs are representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.