

HALE

TRAILER

BRAKE & WHEEL

031024
VIN: 55767



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	TELESCOPIC SEMI-TRAILER, STEEL PLATFORM.
DIMENSIONS	
LENGTH	53'-0" closed.
LENGTH	90'-0" open
OPENINGS	5'-0" increments in closed position.
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 61 1/4" high at front and 58" at rear.
COUPLING	
COUPLER PLATE	5/16", plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	49".
STRUCTURE	Frame with "CAMBER".
FLANGES	Female section, exterior, 3/8" x 6", 100 000 psi steel, 24" high.
FLANGES	Male section (interior), 3/4" x 6", 60 000 psi steel, 17 5/8" high.
WEB	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel.
GOOSENECK	12" high, with integrated nose ramp and 48" straight behind king pin.
CROSSMEMBERS	I beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, 12" centre to centre.
FLOOR	Apitong, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember.
SIDE RAILS	6" channel @ 8.2 lbs/ft.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions).
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
DIAGONAL BRACES	2" x 2" x 3/16" angles, welded in web and to a crossmember, located each side.
X BRACES	Between main beams, full length, sheet metal with cutting holes at front and rear between male main beams.
LOCKS	Air operated with a third glad hand at front.
ROLLERS	4, 2 on female sections of frames and 2 on male sections.
SPACERS FOR RUB RAILS	Double between side boxes.
ENDS	
FRONT RAIL	9 gauge formed steel.
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
REAR RAIL	11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel.
ELECTRICAL	
FRONT CONNECTOR	7 way (SAE J560), Phillips brand.
ELECTRICAL SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108.
MAIN SYSTEM	Grote Ultra Blue LED, grounded to front connector, sealed beams Grote. (tail lights with male pins #54332, markers #47122, 47233 (2 1/2" dia.), licence light #60280-M, with vapor proof junction box Truck-Lite #50400).



ITEM	DESCRIPTION
TURN SIGNAL REAR ADD. CONNECTOR	Sealed beams LED, (Grote #54163), one lamp including side marker and flasher, each side at middle point, amber. 4 way.
LANDING GEAR SAND SHOES CRANK	Holland, Mark V (LGS-4F115). 10" x 11 1/2". Road side.
BOGIE BOGIE SUSPENSION U-BOLTS SPRINGS AXLE(S) SPIDERS CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS TIRES TIRES	Slider, air ride suspension, tridem, 60" spread. Bogie tubing frame for suspension with 9" mounting height. (96" travel) Hendrickson HT-250US (9), tridem, 60" spread. (Use only with slider bogie) With nuts at bottom. Air. AXN, TA250T, 22 500 lbs. capacity. Welded. 28 splines. 77 1/2". None (AXN). 16 1/2" standard, AXN R23 extended life lining. HM 218248 and HM 212049. Meritor, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omnibrake" (30-30). 10 studs disc hubs, outboard mount, 285.75mm B.C., single flange nuts. For dual steel wheels or single wheels. 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes. Continental, 11 R 22.5 HT3 ECO-PLUS 14 ply (41.2") NOTE: "Tires on imports do not qualify for a Fair Market Value Deduct towards F.E.T. calculation".
AIR SYSTEM GLAD HANDS AIR VALVES VALVE VALVE CONTROL BOX DIAGNOSTIC CABLE	Fixed. Meritor Wabco, ABS, 2 sensors 1 modulator. (2) Fast-brake kit. Manual blow down valve in a control box, with auto-reset feature, including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table. Stainless steel, 10" height x 12" width x 6" deep. Applicable with tandem or tridem suspensions. not included with ABS valve.
ACCESSORIES REGISTRATION HOLDER SLIDING TRACK MUD FLAPS	One plastic and aluminum (Grote #43424). Full length, "LL" extruded aluminum, road side. One set, rubber with Manac logo and vertical grooves to reduce spray.



ITEM	DESCRIPTION
FINISHING PAINT	Shot blasted, one coat of epoxy primer and two acrylic urethane top coats, Color: black, code: U-TECH RM 99U.
HUBS	Same color as trailer.
WHEELS OR RIMS	White.
RETROREFLECTIVE TAPES	Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar.
PAINTED AXLES	Same color as trailer.

ADDITIONAL OPTIONS	Ref. #152161*****
---------------------------	-------------------

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.