

HALE TRAILER BRAKE & WHEEL



031957
VIN: 044462

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Little Rock, AR: 833-424-8944
Baltimore, MD: 888-601-7500	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Raleigh, NC: 833-418-9777
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235
Jacksonville, FL: 800-828-3055	Walpole, MA: 800-854-5310

haletrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

TK70EFX Blade Trailer

Standard Equipment
 53' Overall length - closed**
 144'-5" open (includes pull out)
 8'-6" wide
 8'-10" gooseneck length
 Detachable gooseneck
 Low profile gooseneck design
 72" swing clearance
 49" fifth wheel height
 20" long full width front and rear bolsters
 54" front bolster height
 49" rear bolster height
 See quote drawing #072300 for dimensional information
 Rolled aluminum GN fenders with no gap between fender and gooseneck beam
 2 speed landing gear
 Narrow, double telescopic, mono beam, main frame with trapezoidal design
 Center beam lock (lock to keep center be stationary while positioning front beam)
 Draped air and electrical lines w/ chain style securement
 Air and electrical lines in protective nylon sock
 Lock holes on 18" centers

Hydraulic turntable style steering with electric steering stops
 Electric/hydraulic self contained unit w/ 2 batteries
 20 amp DC/DC converter/battery conditioner with two conductor charge wire & single pole sockets

Air ride suspension HT250 with raise and lowering kit
 Spring actuated turntable lock w/ air release
 Wireless remote for steering with antenna mounted at rear w/ hard wired backup and 50' pendant
 2S1M ABS
 10'-1" axle spacing
 Steel disc wheels
 235/75R X 17.5 tires
 Half round aluminum fenders
 Mud flaps on all axles
 4 d-rings on rear bolster
 D.O.T. certified bumper

Flag holders at front and rear, Std

round w/no set screws
 3/4" NPT strobe light holders with 4-way sockets and one off/on switch at rear
 L.E.D. lights (Grote)

3 pair of round flag holders: at front, on rear bolster, and on the pull out
 Air controls located on curb side below rear bolster
 15' rear pull out w/ 5,000 lb capacity
 2 blade tip supports w/ cradle, one to fit the first beam and one to fit the last beam* (53' version only)

*Note: Blade tip supports are rated for 6,000 lbs

**Note: The assistance of a lifting device (fork lift, crane, etc.) is required to open and close the trailer Black with white decals

60788 TK70EFX 24' deck

Paint to be Black

Add 28' jumpers with 4way socket and plug for elec lock pin for trailers

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.