

# HALE

## TRAILER

### BRAKE & WHEEL



031958  
VIN: 054719

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

#### TK70EFX Blade Trailer

Standard Equipment  
53' Overall length - closed\*\*  
144'-5" open (includes pull out)  
8'-6" wide  
8'-10" gooseneck length  
Detachable gooseneck  
Low profile gooseneck design  
72" swing clearance  
49" fifth wheel height  
20" long full width front and rear bolsters  
54" front bolster height  
49" rear bolster height  
See quote drawing #072300 for dimensional information  
Rolled aluminum GN fenders with no gap between fender and gooseneck beam  
2 speed landing gear  
Narrow, double telescopic, mono beam, main frame with trapezoidal design  
Center beam lock (lock to keep center be stationary while positioning front beam)  
Draped air and electrical lines w/ chain style securement  
Air and electrical lines in protective nylon sock  
Lock holes on 18" centers

Hydraulic turntable style steering with electric steering stops  
Electric/hydraulic self contained unit w/ 2 batteries  
20 amp DC/DC converter/battery conditioner with two conductor charge wire & single pole sockets  
Air ride suspension HT250 with raise and lowering kit  
Spring actuated turntable lock w/ air release  
Wireless remote for steering with antenna mounted at rear w/ hard wired backup and 50' pendant  
2S1M ABS  
10'-1" axle spacing  
Steel disc wheels  
235/75R X 17.5 tires  
Half round aluminum fenders  
Mud flaps on all axles  
4 d-rings on rear bolster  
D.O.T. certified bumper  
Flag holders at front and rear, Std round w/no set screws  
Brackets at rear for a removable oversized load sign  
3/4" NPT strobe light holders with 4-way sockets and one off/on switch at rear  
L.E.D. lights (Grote)

3 pair of round flag holders: at front, on rear bolster, and on the pull out  
Air controls located on curb side below rear bolster  
15' rear pull out w/ 5,000 lb capacity  
2 blade tip supports w/ cradle, one to fit the first beam and one to fit the last beam\* (53' version only)  
\*Note: Blade tip supports are rated for 6,000 lbs  
\*\*Note: The assistance of a lifting device (fork lift, crane, etc.) is required to open and close the trailer  
Black with white decals  
60788 TK70EFX 24' deck  
*Paint to be Black*  
Add 28' jumpers with 4way socket and plug for elec lock pin for trailers

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.