

HALE

TRAILER

BRAKE & WHEEL



031959
VIN: 054720

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Little Rock, AR:	833-424-8944
Baltimore, MD:	888-601-7500	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Raleigh, NC:	833-418-9777
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
Jacksonville, FL:	800-828-3055	Walpole, MA:	800-854-5310

haletrailer.com | @haletrailer



800-232-6535 *FINANCING AVAILABLE

TK70EFX Blade Trailer

Standard Equipment

53' Overall length - closed**

144'-5" open (includes pull out)

8'-6" wide

8'-10" gooseneck length

Detachable gooseneck

Low profile gooseneck design

72" swing clearance

49" fifth wheel height

20" long full width front and rear bolsters

54" front bolster height

49" rear bolster height

See quote drawing #072300 for dimensional information

Rolled aluminum GN fenders with no gap between fender and gooseneck beam

2 speed landing gear

Narrow, double telescopic, mono beam, main frame with trapezoidal design

Center beam lock (lock to keep center be stationary while positioning front beam)

Draped air and electrical lines w/ chain style securement

Air and electrical lines in protective nylon sock

Lock holes on 18" centers

Hydraulic turntable style steering with electric steering stops

Electric/hydraulic self contained unit w/ 2 batteries

20 amp DC/DC converter/battery conditioner with two conductor charge wire & single pole sockets

Air ride suspension HT250 with raise and lowering kit

Spring actuated turntable lock w/ air release

Wireless remote for steering with antenna mounted at rear w/ hard wired backup and 50' pendant

2S1M ABS

10'-1" axle spacing

Steel disc wheels

235/75R X 17.5 tires

Half round aluminum fenders

Mud flaps on all axles

4 d-rings on rear bolster

D.O.T. certified bumper

Flag holders at front and rear, Std round w/no set screws

3/4" NPT strobe light holders with 4-way sockets and one off/on switch at rear

L.E.D. lights (Grote)

3 pair of round flag holders: at front, on rear bolster, and on the pull out

Air controls located on curb side below rear bolster

15' rear pull out w/ 5,000 lb capacity

2 blade tip supports w/ cradle, one to fit the first beam and one to fit the last beam* (53' version only)

*Note: Blade tip supports are rated for 6,000 lbs

rated for 6,000 lbs

**Note: The assistance of a lifting device (fork lift, crane, etc.) is required to open and close the trailer Black with white decals

Spray-on truck bed liner, front

60788 TK70EFX 24' deck

Paint to be Black

Add 28' jumpers with 4way socket and plug for elec lock pin for trailers

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.