ETNYRE

Specifications

32469-32471 & 32473-32474

2018 Hydraulic Detachable Lowboy 55 Ton Paver

Model:	RTN55TD3-PS Trailer
Capacity:	55-Tons in any 16’
Construction:	(4) I-Beam, Cambered, T-1 Steel
Custom/Paver Special:	Tapered Front Beams (8 3/8” deep)
Platform Width:	8’6”
Platform Length:	24’ (must hold 53’ O.A.L.)
Platform Height/Road Clearance:	22”/6”
Crossmember Spacing:	On 20” Centers
Auxiliary Crossmembers:	On 10” Centers (outside main beams)
Front Folding Ramps:	41” long – wood filled – adjustable
Frame Reinforcement:	For future 4th closed coupled axle
Hydraulic System:	From Tractor Wet Line
Gooseneck:	Non-Ground Engaging Removable – Hi-Lift
Gooseneck Support Cylinder:	Hydraulic
Gooseneck Connection:	Pin & Stirrup type w/Vertical Air Lock Pin
Fifth Wheel Height:	48”-50”-52”-54”-56” Loaded (adjustable)
Swing Clearance:	108” & 84” Dual King Pin Settings
1/8” Aluminum Top Cover:	Over gooseneck area
Air Brakes:	16.5” x 7” w/ Auto Slacks & Outboard Drums
Anti-Lock Brakes:	None (Trailer GVWR exceeds 120,000#)
Spring Brakes:	On 1 axles
Axles:	(3) 25,000#, ¾” Wall
Tires:	(12) 275/70R 22.5 (H)
Aluminum Wheels (Polished Outers) &:	Steel Disc inners, 10-Hole, Hub Piloted, 8.25” x 22.5”
Suspension:	Ridewell Air Ride w/ 50” axle spacing
Suspension:	+3/-3 Height Control, auto/manual
Manual Exhaust Valve:	Knob Style
Axle Air Lift:	on 3rd axle
Lights:	LED Truck-Lite Rubber Sealed System
Flasher Kit:	Rear warning lights with rechargeable battery flash all lights w/switch for strobes when traveling
3rd Tail Light Package:	Amber LED strobes for warning lamps
Air & electrical:	@rear for future 4th axle
Lash Rings:	(16) Total – 6 per side (bent style), 1 each bolster end,(flat style)
Extension Brackets (Outriggers):	12” Swinging/removable w/ dbl. hook-on
Decking:	1 1/2” Apitong – full width
Paint:	**GLOSS BLACK** (2-part Urethane)
Chain Hook & Flag Holder Slots:	On bolsters
Storage Basket:	(1) 2nd section from front
Rear Deck:	Wood covered, 1 -1/2” Apitong (full width)
Special Rear Slope (Main to Rear Deck):	3:1 – 18.64 degree wood filled-(full width)
Roller Stop @ Rear:	4” high, width of main beams

Disclaimer
Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are representative of the subject equipment, but may not be identical. Equipment availability, prices and specifications are subject to change without notice.