



Hale Trailer Brake & Wheel

035241

MODEL: XL120SDE DIST: 120000# CONC. 100,000# IN 10' CLOSED 53' OAW: 102"
X-L SPECIALIZED TRAILERS, INC. WEIGHT +/-3%= 22,900

GOOSENECK-

LENGTH: 11' 6" NARROW GOOSENECK
KING PIN SETTING: 16"
SWING CLEARANCE: 102"
5TH WHEEL HEIGHT: 52"
DECKING: NONE
STAKE POCKETS: NONE
LANDING GEAR: 2 SPEED, HANDLE ON ROADSIDE
FLIP NECK: FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR 66" FLIP NECK EXTENSION
66" FLIP NECK

MAIN DECK-

LENGTH: 41' 6" EXTENDING TO 64' 4"
LOADED DECK HGT: 33" OPEN WHEELS
DECKING: 1 1/8" APITONG DECKING FLUSH
CROSSMEMBER: 4" JR. I-BEAM ON 12" CTRS.
SIDE BEAMS: 6" MILL CHANNEL
STAKE POCKETS: 24" O/C, 5/16" X 2" RUB RAIL W/ SINGLE PIPE SPOOLS
D-RINGS: 7 PAIR OF PAN STYLE D-RINGS ON MAIN DECK--EVENLY SPACED
7 PAIR OF FLAT D-RINGS AT BOTTOM OF KNEE BRACES

REAR DECK:

LENGTH: 33"
LOADED DECK HEIGHT: 33"
AXLES: (3) 25,000 NOMINAL, 77 1/2" TRACKING LIMIT CHAINS ON ALL 3 AXLES
SUSPENSION: HEND-TURNER/25,000 AIR
AXLE SPACING: 60"
ABS: N/A SPRING BRAKES ON 1 AXLE
TIRES: MICHELIN 245/70R/17.5
WHEELS: 6.75 X 17.5 STEEL INSIDE, ALUMINUM POLISHED OUT DISC WHEELS
BRAKES: 12 1/4" X 7 1/2"
DRUMS: HUB PILOT/ OUTBOARD DRUMS
ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAILLIGHT ALUMINUM PACKAGE
MANUAL RIDE HEIGHT CONTROL
1 PAIR OF BENT D-RINGS IN TAIL CHANNEL

ADDITIONAL:

PAINT: BLACK URETHANE WITH 2 PART EPOXY PRIMER
1 EXTRA LIGHT PER SIDE AT START OF MAIN DECK
FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR 2 AXLE POWER BOOSTER
4" AMBER STROBE LIGHT TO BE USED AS 3RD TAIL LIGHT
DUST SHIELDS
(1) 4 WAY PLUG IN EACH CORNER OF MAIN DECK
PSI TIRE INFLATION SYSTEM ON ALL 3 AXLES
LIQUID FILLED AIR GAUGE AND RAISE AND LOWER VALVE MOUNTED IN BOLSTER
(1) 4 WAY PLUG IN REAR BOLSTER - BOTH SIDES

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.