



Trailer Specifications

Talbert 2018

36971-Flip Axle

Model: T (3)J-275/70R22.5

Capacity in tons: 65

Gooseneck design	FG
Loaded kingpin height	52"
Sliding 5th wheel	72"
Sliding 5th wheel height	52"
Swing radius	104" with removable kingpin settings at 104" & 88"
Electrical receptacle	Seven pin connector
Additional gooseneck specifications	Two (2) speed landing gear
Gooseneck/deck connection	Fixed/welded
Rear bridge section width	8'-0"
Number of axles	2 - 25,000# Capacity GAWR = 24,700#
Axle spacing	60"
Brakes	16-1/2" x 7" air actuated with spring brakes on one axle
Wheels	Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels Dura-Bright
Tires	Eight (8) 275/70R22.5 (H) 16PR radials
Suspension	Ridewell air ride with 2nd axle removable (S/N 36971) Chrome tapered connecting pins
Suspension options	1) - Manual exhaust 2) - Liquid filled air gauge in first axle curb side air bag with conversion decal
Lights and wiring	12 volt LED system with license plate light regular Mid-turn each side
Paint	Valspar standard Talbert black
Lash rings	4 Total 1 each side of the gooseneck and 1 each side between axles
Estimated empty weight	8,680#
Compatibility	For use with 180" & 190" swing radius and 3rd intermediate axle (REF S/N
Design notes	5th Wheel set 140" from the 104" radius setting. 5th Wheel set 125" to center line of tandem.
Additional design specifications	1) - Limit chains on both axles 2) - Plate for Hydroneck support cylinder 3) - Pogo stick to support air/electrical/hydraulic lines

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.