

# HALE TRAILER BRAKE & WHEEL



037886  
VIN: G8464N

## SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b> 800-383-8894	<b>Little Rock, AR:</b> 833-424-8944
<b>Baltimore, MD:</b> 888-601-7500	<b>Portland, ME:</b> 800-325-4253
<b>Concord, NC:</b> 800-438-2250	<b>Raleigh, NC:</b> 833-418-9777
<b>Delmar, DE:</b> 866-486-1400	<b>Scranton, PA:</b> 800-569-1400
<b>Des Moines, IA:</b> 888-673-5011	<b>Springfield, MA:</b> 800-854-5306
<b>Elkton, MD:</b> 800-544-7127	<b>Voorhees, NJ:</b> 866-315-0235
<b>Jacksonville, FL:</b> 800-828-3055	<b>Walpole, MA:</b> 800-854-5310

haletrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

### TK80J Jeep; No ABS, 80,000lb cap (2 axles)

#### STANDARD EQUIPMENT

Outboard 10-hole pilot mount  
27,000 lb. axles (3/4" wall)  
Chain ups for axle  
16 1/2" x 7" air Brakes  
Oil seal hubs  
Air ride suspension  
Automatic slack adjusters

Electrical system per ICC/DOT regulations  
Rubber mounted sealed LED lights and sealed harness system  
Telescopic pin-type park stands  
48" sliding 5th wheel  
Mud flaps  
Liquid-filled air gauge  
Air ride raise and lowering kit  
Pogo stick for air and electrical lines  
Four (4) D-rings for lifting  
Red & white conspicuity markings  
Color: Trail King 2-part polyurethane

### 11939-TK80J

1	11939	Open Deck	TK80J Jeep; No ABS, 80,000lb cap (2 axles)
1	11958	Fifth Wheel	50" 5th-wheel height
1	11962	Fifth Wheel / King Pin	16" kingpin setting w/84" swing clearance <i>KP settings at 16" and 28"</i>
1	11966	Hydraulics	No hydraulics through jeep
1	11978	Landing Gear	2-speed park stands (crank handle on curb side)
1	11980	Width	8' 6" wide (80J)
1	11992	Axle Spacing	60" axle spacing

1	11994	Hub / Drum	Steel hub-piloted - cast drum (per complete axle)
8	08180	Wheel Size	6.75 x 17.5 8-hole disc wheel ILO Std 8.25 x 22.5 10-hole disc wheel (per wheel)
4	08183	Wheel Finish (inside)	6.75 x 17.5 machined aluminum ILO Std steel wheels (per wheel)
4	08194	Wheel Finish (outside)	6.75 x 17.5 polished aluminum ILO Std steel wheels (per wheel)
8	08135	Tire Size	235/75R17.5 - 16 ply in lieu of STD 275/70R22.5 - 16 ply (per tire)
1	08024	Paint	Black S7203 with white decals (735-432-039)

### 11939-Additional Options

8	08036	Alternative Tire Brand	Michelin 235/75R17.5 - 16 ply XTE2 in lieu of STD 235/75R17.5 - 16 ply (per tire)
1	62958	Miscellaneous	Stainless steel insert in tail channel
1	11963	Fifth Wheel / King Pin	Two kingpin settings (specify additional setting) <i>16" &amp; 28" KP setting</i> <i>110" &amp; 98" swing cl.</i> <i>267" between first KP setting &amp; center of axles</i>
1	9999-01	Custom Options	Goes with TK80J E3448, TK120HED E3449, TKFA1 E3450 & TKHB2 E3451

### **TK120HED Hydraulic GN, extendable deck, 29'6" closed length - approx 50'4" open, 24" loaded deck height with 6" ground clearance, No ABS. (2) axle unit (53'6" OAL MAX**

#### STANDARD EQUIPMENT

3 - 27,000 lb. axles (3/4" wall)  
16 1/2" x 7" air Brakes  
8.25 x 22.5 disc wheels  
Outboard 10-hole pilot mount  
275/70R x 22.5 16PR radial tires (H)  
Oil seals  
16" kingpin setting  
Hydraulic self-lifting detachable gooseneck  
(can lift above or below transport positions)  
Hydraulic gooseneck support arm  
Air control panel - includes a liquid-filled air gauge  
Air-activated, positive self-locking pin on gooseneck

Gooseneck does not require ground bearing pads for lifting  
4-beam main frame construction  
Automatic slack adjusters  
10" I-beam crossmembers on 24" centers  
50" loaded 5th wheel height  
Mid-turn signal/clearance light  
Rubber mounted sealed lights and harness system  
Electrical system per DOT regulations  
7-pole electrical connector  
Mud flaps  
Red & white conspicuity markings

## 11528-TK120HED

1	64095	Open Deck	TK120HED Hydraulic GN, extendable deck, 29'6" closed length - approx 50'4" open, 24" loaded deck height with 6" ground clearance, No ABS. (2) axle unit
1	64095	Hydraulic Gooseneck	Alternative Option Selected. See Add'l Options Section Below. <i>12'6" Base GN with KP settings at 16" with 102" swing clearance, and 40" KP setting with 78" of swing clearance. 75" GN Flip with 16" KP setting with additional setting at 32".</i>
1	11537	Fifth Wheel	50" 5th-wheel height
1	11542	Hydraulics	PTO hydraulic
1	11547	Deck Width	102" deck width
1	9998	Main Deck	24" loaded deck height with 6" of ground clearance
1	11552	Main Deck	Swing-out outriggers with planks
1	9998	Main Deck	12" deep I-beam style outside beam with 4 additional pair of bent style D-rings <i>29'6" closed approx 50'4" open</i>
1	11558	Main Deck	Bent style d-rings on load deck (5 pair std)
1	11570	Decking	1 3/4" Apitong raised decking (net)
1	11575	Ramps	31" high capacity front loading ramp
1	11576	Ramps	No rear ramp
1	11580	Wheel Area	Bolster style wheel area
1	11583	Wheel Area	Formed bolster
1	11588	Wheel Area	Detachable wheel area with horizontal pins (adds 6" to oal) - with bolt-on front bolster
1	11591	Wheel Area	No beavertail
1	9998	Concentrated Capacity	100,000 Lbs. in 10'
1	11607	Suspensions	Air ride suspension

1	11609	Axles	No lift axle
1	11625	Axle Spacing	60" axle spacing (adds to OAL) Air-ride
1	11628	Hub / Drum	Steel hub-piloted - cast drum (per complete axle)
1	08180	Wheel Size	6.75 x 17.5 8-hole disc wheel ILO Std 8.25 x 22.5 10-hole disc wheel (per wheel)
4	08193	Wheel Finish (inside)	6.75 x 17.5 machined aluminum ILO Std steel wheels (per wheel)
4	08194	Wheel Finish (outside)	6.75 x 17.5 polished aluminum ILO Std steel wheels (per wheel)
8	08135	Tire Size	235/75R17.5 - 16 ply in lieu of STD 275/70R22.5 - 16 ply (per tire)
1	11637	Lights	LED light package (5th-wheel)
1	08024	Paint	Black S7203 with white decals (735-432-039)

### 11528-Additional Options

1	11601	Frame Reinforcement	Frame reinforcing for tandem axle booster
1	11640	Lights	3rd Tail Light Package
1	11635	Electrical	4-pole electrical socket at rear wired to clearance light
1	11648	Miscellaneous	Brackets only for Removable oversized load sign
1	11649	Miscellaneous	Removable oversized load sign (includes. signage)
1	11602	Frame Reinforcement	Brackets, electrical, and air connections at rear for add'l axles
2	11646	Miscellaneous	Flag holders (per pr.)

*Front of load deck and rear of trailer*

1	11541	King Pin Plate	Additional kingpin settings (Ea.) (specify setting) <i>Additional KP setting on Base G to be 40" and Flip Gn to be 32"</i>
1	11077	Main Deck	Auto Track ( air and electrical in protective track)
1	9999-04	Custom Options	2 bent style d-rings on tail channel
1	9999-05	Custom Options	TK120HED ILO 120HDG option with 31" loaded wheel area height with axles through the frame design, open bolster style wheel area with steel covering center bay of wheel
1	9999-01	Hydraulics	16 HP Vanguard self-contained power unit - Included in Base Price
2	11817	Miscellaneous	Stainless steel insert in tail channel (on trailer and flip axle, covering 4" strokes and 3rd taillight)
1	64095	Custom Options	6" stub crossmember in outer bays for crossmembers 12" O.C.
1	62278	Custom Options	62278 - TK120HDG - Add 3rd taillight package and add 4"amber strokes (4 lights per side)
1	9999-03	Custom Options	Goes with TK80J E3448, TK120HED E3449, TKFA1 E3450 & TKHB2 E3451
8	08033	Custom Options	Michelin 235/75R17.5 - 16 ply XTE2 in lieu of STD 235/75R17.5 - 16 ply (per tire) on TK120HED

## TKFA1 Flip Axle (3rd flip ILO fixed)

### 10988 - STANDARD EQUIPMENT

Pan style design

Air ride suspension

Automatic slack adjusters

8.25 x 22.5 10-hole disc wheel

One-piece axle seals

Pro tork axle nuts

LED lights, 50 state legal

Electrical system per DOT regulations

Flagholders

Wide Load sign brackets

(2) D-rings on rear channel

Rubber mounted sealed lights with sealed harness system

Mudflaps

Red and white conspicuity markings

Paint: Trail King 2-part polyurethane

### 10988-TKFA1 (3rd flip ILO fixed)

1	10988	Open Deck	TKFA1 Flip Axle (3rd flip ILO fixed) <i>no chain ups</i>
1	10990	Axle Spacing	60" axle spacing
1	10991	Overall Width	102" overall width
1	10993	Beam Depth	For correct Flip Axle beam depth, specify the Serial # of the corresponding trailer.
1	9998	Position	Alternative Option Selected. See Add'l Options Section Below.
1	10997	Flip Axle Styles	Open wheels with load bearing tail channel
1	11004	Upper Bracket Style	Upper Links for trailers other than HDG ADV Plus
1	11007	Axles	27,000 lb (3/4" wall) axle
1	9998	Brakes	Alternative Option Selected. See Add'l Options Section Below.
1	11008	Hub / Drum	Steel hub-piloted - Cast drum
1	9998	Wheel Finish (inside)	Alternative Option Selected. See Add'l Options Section Below.
1	9998	Wheel Finish (outside)	Alternative Option Selected. See Add'l Options Section Below.
1	9998	Tire Size	Alternative Option Selected. See Add'l Options Section Below.
1	11013	Lights / Electrical	3rd Tail Light Package
1	08024	Paint	Black S7203 with white decals (735-432-039)

## 10988-Additional Options

2	63718	Custom Options	#63718 - 17.5 Machine finish alum. Wheels inboard ILO STD 22.5 steel disc
2	63718	Custom Options	#63718 - 17.5 Polished finish alum. Wheels inboard ILO STD 22.5 steel disc
4	08033	Custom Options	Michelin 235/75R17.5 - 16 ply XTE2 in lieu of STD 235/75R17.5 - 16 ply (per tire)
1	62563	Custom Options	#62563 - TKFA1 - Add 4" amber strobes (in addition to the 3rd tail light package)
1	61078	Custom Options	#61078 TKFA1 1 D-ring centered on the front cross tube for lifting.
1	63718	Custom Options	#63718 - Intermediate flip axle, reinforced for and tandem axle Air or Hyd booster, axles through the frame design, 102" wide,
1	9999-08	Custom Options	Goes with TK80J E3448, TK120HED E3449, TKFA1 E3450 & TKHB2 E3451

### TKHB2 Fixed Axle

#### STANDARD EQUIPMENT

Two (2) fixed 27,000-lb. axles (¾" wall)  
Chain-ups for axles  
16 1/2" x 7" air brakes  
8.25 x 22.5 disc wheels  
Air ride suspension  
Raising/lowering air control panel  
Dump valve

Drop-leg jack  
Oil seal hubs  
Flag holders at rear  
Wide Load sign brackets  
Rubber mounted sealed LED lights  
and sealed harness system  
Electrical system per ICC/DOT regulations  
Lifting eye and D-rings for loading  
Red & white conspicuity markings  
Color: Trail King 2-part polyurethane

## 11781-Base

1	11781	Open Deck	TKHB2 Fixed Axle <i>38" frame height through booster</i>
1	11784	Width	102" wide
1	11792	Axle Spacing	60" axle spacing
1	11793	Axle Spacing	14' 1" axle spacing from center of the last axle on the trailer to the first axle on the booster
1	11795	Brakes / Air	2S1M Anti-Lock Brake System
1	11798	Hub / Drum	Steel hub-piloted - cast drum (per complete axle)
8	08180	Wheel Size	6.75 x 17.5 8-hole disc wheel ILO Std 8.25 x 22.5 10-hole disc wheel (per wheel)
4	08183	Wheel Finish (inside)	6.75 x 17.5 machined aluminum ILO Std steel wheels (per wheel)
4	08194	Wheel Finish (outside)	6.75 x 17.5 polished aluminum ILO Std steel wheels (per wheel)
8	08135	Tire Size	235/75R17.5 - 16 ply in lieu of STD 275/70R22.5 - 16 ply (per tire)
1	11810	Lights	3rd Tail Light Package
1	11815	Miscellaneous	5 ½ HP self-contained unit
1	08024	Paint	Black S7203 with white decals (735-432-039)

## 11781-Additional Options

8	08036	Alternative Tire Brand	Michelin 235/75R17.5 - 16 ply XTE2 in lieu of STD 235/75R17.5 - 16 ply (per tire) on Booster
1	11817	Miscellaneous	Stainless steel insert in tail channel
1	62416	Custom Options	62416, Boosters, 3rd tail light package and amber strobe lights with switch (4 lights per side)
1	9999-03	Custom Options	Goes with TK80J E3448, TK120HED E3449, TKFA1 E3450 & TKHB2 E3451

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.