



## Hale Trailer Brake & Wheel 038663

### Talbert Manufacturing, Inc.

**Model:** AC3-25-AR (air)

**Capacity in tons:** 25

|                                   |  |
|-----------------------------------|--|
| Pintle eye                        | Adjustable pintle eye (3" I.D.) with 48" chain and grab hooks  |
| Tongue                            | 5'-6" with lockable tool box with aluminum diamond plate lid<br>Move hinge 4" forward  |
| Landing Gear                      | 2-speed, 50,000# crank down dual landing leg, mounted to main beams and headboard  |
| Electrical receptacle             | Seven pin connector  |
| Headboard                         | 8" high full width   |
| Deck section design               | One piece tongue, main beam and beavertail (cold formed)   |
| Deck section length               | 32'-0" (26'-0" flat with 6'-0" beavertail)   |
| Deck section width                | 8'-6"  |
| Loaded deck height                | 32-3/4"  |
| Flooring                          | 1-1/2" apitong   |
| Lash rings                        | 16 total -<br>6 each side on flat deck (straight style), 12 total<br>2 each side on beavertail, one toward top and one towards bottom, (straight style), 2 total |
| Mainbeams                         | 12" deep hi-tensile  |
| Crossmembers                      | 6" deep hi-tensile   |
| Sidemembers                       | 8" deep hi-tensile   |
| Beavertail                        | 6'-0" with wood flooring full width  |
| Ramps                             | 38" wide x 6'-0" length air ramps with wood flooring, stored vertically with lock  |
| Number of axles                   | 3  |
| Axle capacity                     | 25,000#  |
| Brakes                            | 12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on two axles.   |
| Wheels                            | Steel disc with oil seals (6.75 x 17.5)  |
| Tires                             | Twelve (12) 215/75R17.5 (H) 16PR radials<br>Use valve stem extensions on inside wheels   |
| Suspension                        | Air ride with air lift on axle 1<br>Air lift switch located on tongue<br>44,800# Hutch spring on axles 2 & 3   |
| Lights and wiring                 | 12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK  |
| Paint                             | Valspar standard Talbert black   |
| Estimated empty weight            | 12,560#  |
| Additional general specifications | Formed step in front of 1st axle both sides of trailer   |

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.