



**Hale Trailer Brake & Wheel
039942**

Talbert Manufacturing, Inc.

Model: AC-12 (air)

Capacity in tons: 12

Pintle eye	Adjustable pintle eye (3" ID) with 48" chain and grab hooks
Tongue	5'-6"
	No tool box
1 Landing Gear	Install one (1) two speed jack, JSTA400R.G1.17.02.57 with 302C09001 mounting plate in center of tongue
	Ship one (1) two speed jack, JSTA400R.G1.17.02.57, one (1) single speed HHLGD700-21/HHLG0083-09 and two (2) mounting plates 302C09001 loose for customer installation.
	No rear jacks or jack mounting structure installed. Enclose area where rear jacks were installed with smooth plate.
Electrical receptacle	Seven pin connector
Headboard	None
Deck section design	Flat deck
Deck section length	35'-0" Maximum length, not including tongue
Deck section width	8'-6"
Loaded deck height	32-1/4"
Flooring	None, 1/4" formed smooth plate installed for shelter installation. 1/4" Smooth plate over tires. All other areas open.
Lash rings	4 each side
Crossmembers	6" deep hi-tensile
Mainbeams	12" deep hi-tensile
Sidemembers	8" deep hi-tensile
Beavertail	None
Ramps	None
Number of axles	2
Axle capacity	25,000#
Brakes	12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brake on all axles.
Wheels	Steel disc with oil seals (6.75 x 17.5)
Tires	Eight (8) 215/75R17.5 (H) 16PR radials Use valve stem extensions on inside wheels
Suspension	Ridewell air ride suspension with manual exhaust valve, switch mounted in light panel
Lights and wiring	12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK 3 markers each side including a mid-turn light Note: provide a 7-way plug connection between tongue and deck
Paint	Valspar standard Talbert black
1 Additional general specifications	None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.