

# ***EAST***

**2017**

## ***HARDOX – STEEL FRAME DUMP TRAILER w/Steerable Lift***

**56793**

### **BODY SPECIFICATIONS**

LENGTH: 34' Steel Tub  
WIDTH: 96"  
SIDE HEIGHT: 66" + Angle (1)  
SIDE MATERIAL: ¼" AR450  
TOP RAIL: ¼" x 4" x 8"  
SIDE OPTIONS: 3" x 3" Angle on Top Rails  
FLOOR MATERIAL: ¼" AR-450 Ref 45212  
CROSSMEMBER 12"  
SPACING:  
FLOOR OPTIONS: None  
TAILGATE CONTROL: Air /Frame Switch  
BODY PACKAGE None  
OPTIONS:  
VIBRATOR: None  
MUDFLAPS: Standard & across rear chassis  
TARP BARS: None  
TARP: None  
BOW HOLDERS: None  
TARP BOWS: None  
TARP BASKET: None  
TARP HOOKS: See Note (2)  
BULKHEAD MATERIAL: ¼" AR-450 (Slope Nose)  
BULKHEAD: None  
BULKHEAD OPTIONS:  
BODY FENDERS: Square off w/Flap  
LADDERS: Outside-Front & Rear D/S - Inside-None  
SHOVEL HANGER: Front P/S  
DIRT SHEDDERS: Steel Side Skirt – Full Length  
LIGHT PANEL: Full – LED  
¼" x 4" light shield  
MARKER LIGHTS: LED – Front & Rear+  
MMTS: LED center marker /turn  
APRON: None  
BODY ACCESSORIES: None

### **TAILGATE**

HEIGHT: Full  
MATERIAL THICKNESS: 3/16" AR-450  
SLOPE: None  
HINGES: Overslung  
SIDE SWING: Yes w/Ground Control  
GATE SEAL: None  
SAFETY LATCH: 1 each side  
COAL/GRAIN DOOR: None

### **DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

COAL CHUTE: None  
GATE OPTIONS: Strap across bottom

**CHASSIS SPECIFICATIONS**

MODEL: Tandem  
BEAM MATERIAL: 16" Steel – 31#/Ft.  
LENGTH: 34'  
WIDTH: 96"  
HOIST: 85-265  
CHASSIS NECK: Standard  
KINGPIN SETTING: 18"  
5<sup>TH</sup> WHEEL PLATE: ½" w/HD Hoist Mount  
5TH WHEEL HEIGHT: 49"  
OVERHANG: 6"  
REAR AXLE SETTING: 21 ½"  
KINGPIN TO REAR: 368 ½"  
AXLE:  
SUSPENSION: Watson SM-60 SP  
SUSPENSION CONTROL: None  
SUSPENSION SPACING: Standard  
SUSPENSION OPTIONS: None  
SPRINGS: SM-60 60,000#  
AXLES: TP Spindles  
AXLE ACCESSORIES: 25K Rated (3)  
BRAKES: 16-1/2" x 7"  
DRUMS: Cast  
HUBS: 10 Stud Steel Piloted  
WHEELS: 8.25 x 24.5 Steel Disc  
TIRES: 11R x 24.5" Dnlop Sp160 16-ply  
ABS: 4S/2M  
INDEPENDENT SUSPENSION: Crossmember only for 3<sup>rd</sup> Axle – HT250  
DISTANCE: 103" from Rear Axle  
IMT Steerable Lift: Two-9" 22.5" Aluminum Wheels CB  
Two-315/65R 22.5" M860A Tires  
TIRE CARRIER: One – P/S access  
LANDING GEAR: 2 speed Jost A-440 – D/S Crank  
CHASSIS LIGHTS: None  
ELECTRIC COUPLER: 7-Way  
HYDRAULIC TANK: None  
HYDRAULIC HOSE: Wingnut  
FITTING:  
HYDRAULIC HOSE: 108"  
LENGTH:  
TOW HOOKS: None  
PAINT: Body-**BLACK**, Frame-**BLACK**  
REFLECTIVE TAPE (Tarp Bar Tape): None  
CHASSIS OPTIONS: Mudflap on Chassis

**REMARKS:**

- (1) No Center Bolster
- (2) Tarp Hooks: Burnout Design – See engineering for locations - 8 each side + 4 front & rear
- (3) 25,000# rated long stroke chambers and slacks

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.