

# HALE

## TRAILER

### BRAKE & WHEEL

## Hale Trailer Brake & Wheel 063588



=====  
We propose to furnish the following described equipment, material and services at prices, terms and delivery set forth below:

PEERLESS TRANSPORT SEMI: Dual Axle, Live Floor, 45' Length, 15.1 Units

STANDARD SPECIFICATIONS: **CTSSF-45**

Type: Peerless dual axle, transport semi-trailer

Design: Box design, flat floor, end dump, live floor

Construction: .063 prepainted white skin stressed aluminum, last 2 rows of skins to have .125 prepainted white skins (2 on each side), aluminum exterior posts (14.5" centers)

Rails: Top and bottom rails to be one piece extruded aluminum

Unloading Time: Approximately 8 minutes

Capacity: 15.1 units (111.2 cu yd)

Dimensions: 45' long, 8'6" wide, 12'4" high (12'10" top of the arch, 37" king pin location, 36" rear axle from rear of trailer)

Tires: Eight (8) 11:00 X 22.5 radial tires

Wheels: Eight (8) 22.5 x 8.25 - 10 hole, 11 1/4" B.C. steel unimount wheels

Tire Inflation: None

Axles: 25,000# cap., 77 1/2" track, 10 stud, 11 1/4" B.C. hubs, outboard drums, oil seals, quick change brake shoes, auto slacks, HP spindles (same inner & outer bearings)

Brakes: 16 1/2" x 7" air, CM18 lining, type 3030 air chambers, DOT relay emergency system

A.B.S.: 2 sensor - 1 module

Suspension: Four spring three leaf tandem (Hutch H9700T Heavy Duty) with slider

Landing Gear: Two speed, crank on driver's side (Binkley)

King Pin: Standard SAE, heat treated, 37" setting 49" height

Cross Sills & Decking: Hallco 3/16", 6000 series two way standard live floor, 4" Jr. I-Beams on 12" centers with aluminum sub-deck, 3.5" drive, aluminum cross members with 8" spacing over suspension, Hale to furnish floor - KNL to install

Top: Flat design, open top, five center ties (bolted type)



- Top Cover: **Shur lok roll over tarp, black in color, 6" arched tarp bows and caps, telescoping pole with flex handle cut flush at rear**
- Rear Door: **Full opening, side hinged, solid freight doors with mill finish aluminum skins and stainless steel hardware, 6" arched doors and header**
- Rear Frame: **Header, door frame and bumper to be stainless steel**
- Ladders: **Aluminum front ladder only/ none at rear**
- Mud Flaps: **Legal, rubber**
- Wiring: **Unitized wiring system, 12 volt**
- Hook-ups: **Air line hook-ups mounted on driver's side, hydraulic hook-ups on curb side**
- Lights: **Four (4) legal DOT combination stop, tail and directional lights. Legal DOT clearance lights, (2) back up lights – mounted in bumper, (2) work lights on inside front wired to front in waterproof switch, all lights to be LED**
- Reflectors: **Legal DOT**
- Paint: **Aluminum white, steel components primed and painted black**
- Weight: **Approximately 13,543#**

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.