

Hale Trailer Brake & Wheel 071223



		BODY	SPECIFICATIONS		
Langth	26! (4)	I	SFECII ICATIONS	Dody	
Length Width	36' (1) 96" INBOARD	T	NONE	Body Accessories	NONE
		Tarp	NONE	Accessories	NONE
Side Height	64" SOLID	Bow Holders	NONE	-	
Top Rail Side Matl-front	9" DUMP	Tarp Books	NONE		
	4'100 WALL	Tarp Basket	NONE		
-middle	26'140 WALL	Tarp Hooks	NONE		TAILGATE
-rear	6'180 WALL	Bulkhead Mat'l	3/16" (1)	Height	FULL - GENESIS (1)
Side Options	NONE	Bulkhead	5" SLOPE PLATES	Mat'l Thkness	.140 WALL
Floor Mat'l	1/4"	Options	D/S-MANDOOR	Slope	NONE
		Body Fenders	6"	Hinges	OVERSLUNG
Crsmbr Spacing	12"	Ladders (Out)	D/S-REAR	Side Swing	YES - W/ GRD CTRL-P/S HING
				Gateseal	RUBBER
Floor Options	STUB LONGITUDINALS	Inside	NONE	1	
				Safety Latch	ONE EACH SIDE
		Shovel Hgr	NONE		
Tailgate Control	AIR / FRAME+ELEC CC (3)(5)			Coal/Grain Door	NONE
Body Pkg	FOUR PR BODY GUIDES	Light Panel	FULL - LED; X=LED BU LIGHTS		
Options			000X 000 X000	Coal Chute	NONE
Vibrator	NONE	Marker Lights	LED - 14 PR BOTTOM + TOP	Gate Options	NONE
Mudflaps	STD + (1)	MMTS	BELOW RAIL - LED		
	ACROSS CHASSIS REAR	Apron	NONE		
CHASSIS SPECIFICATIONS					
Model	TRIAXLE (FRONT 2 LIFT)	ABS	2S / 1M	Tire Carrier	NONE
Beam Mat'l	ALUMINUM			Landing Gear	2 SPEED JOST AX150
Length	36'				D/S CRANK
Width	96"	Independ. Susp(s)	Chassis Lights	NONE
Hoist	85-265 (2)(6)		NONE		
Chassis Neck	STD			Elec Coupler	7 WAY + ISO 7 WAY
King Pin Setting	18"	Distance:			
5th Whl Plate	3/8" W/ 3/8"X3"X7" MOUNT	From:		Hyd Tank	NONE
5th Whl Ht	49"			Hyd Hose Fitting	WINGNUT
Overhang	6"	Controls		Hyd Hose Length	108"
Rear Axle Setting	21.5"			Tow Hooks	NONE
K/P To Rear Axle	392.5"			Paint	BLACK
Suspension	AAT30K/E3-2 L LIFT-E1 (3)(4)	Location			
Susp Control	FRM SWITCH+ELEC CC (3)(5				NONE
Susp Spacing	52"				
Susp Options	GALVANIZED HANGERS	Accessories		Chassis	* TAPERED REAR
Springs	AIR			Options:	CROSSMEMBER
Axles	TP SPINDLES; 23,000 GAWR	Brakes			W/ DIAMOND PLATE CVR
Accessories	NONE	Drums			
Brakes	16-1/2" x 7"	Hubs			
Drums	CAST				
Hubs	10 STUD STEEL	Wheels			
Wheels	8.25 x 24.5 6 CB IN/ 6 DURA OUT	Tires		• • • • • • • • • • • • • • • • • • •	
Tires	11R 24.5 R250ED H 16 PLY BS(8)				
		-		-	

REMARKS:

- 1. BLACK RUBBER FLAP ACROSS CHASSIS AHEAD OF AXLE 1. **NO WELD ON LOGOS-DECALS ONLY** WEIGHT: 14,772
- 2. REMOTE GREASE ZERKS FROM TOP PIN TO BOTTOM D/S FACING FORWARD
- 3. SEPARATE FRAME SWITCHES AND ELEC CC'S FOR EACH LIFT AXLE
- 4. SEPARATE BRAKE RELEASE FOR EACH LIFT AXLE -(BRAKES DO NOT APPLY WHEN AXLE IS RAISED).
- 5. ONE POLYCARBONATE BOX FOR FRAME SWITCHES LOCATED NEAR D/S LANDING GEAR.
- 6. HOIST ACCESS FROM DOGHOUSE, NO ACCESS ON THE BULKHEAD.
- 7. NO CROSSOVER KIT FOR SUSPENSION
- 8. TIREMAXX PRO PSI SYSTEM ON ALL THREE AXLES.