



# Hale Trailer Brake & Wheel

072109



## EAST GENESIS UNLOADER TRAILER

"GENESIS"

OPEN TOP

CLOSED TOP

BODY:		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TRIAxLE(10)(11)(12)
LENGTH (FEET)	50	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	104"	STYLE	GENESIS	AXLE TO AXLE	60" - 60"
SIDE MAT'L (OUTBOARD)	"GENESIS"	MAT'L THICKNESS	0.150	REAR AXLE SETTING	51"
FRONT	0.150	S / S HINGE ON	P/S 4-3-4	5TH WHEEL HT	51"
MIDDLE	0.150	GATESEAL	NONE	PIN SETTING	36" w / 3/8" PLATE
REAR	0.150	GATE LADDER	Commercial- Ctr	SUSPENSION	AAT30K/E3-2-1 (15)
POLISHED SIDES	NO	TARP HOOKS	NONE	SPRINGS	AIR/GALV HANGERS
ROOF	NONE	WINDERS	ONE - D/S	AXLES	TP
ROOF MAT'L	NONE	GATE GUIDE	YES	BRAKES	MAXX 22T ADB
BULKHEAD	3/16" (1)(2)(3)	GATE CONTROL	MECH	DUSTSHIELDS	N/A
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	STD
TARP BASKET	NONE	CROSSPIPE (S)	TWO MIDDLE -	ABS	2S / 1M
TARP	NONE		SPRING TYPE -	HUBS	10 STUD LW STEEL
CATWALK	YES -FULL WIDTH		REAR TUBE TYPE		HXL5
B.H. LADDER	Commercial D/S	COMPACTOR:		WHEELS	8.25 x 24.5
CROSSMEMBER	"I"BEAM- 12" C/L	SIDE LATCH	N/A		6CB/6 POL
FLOOR MAKE	KEITH 3.5" Drives(4)	CENTER LATCH		TIRES	11R 24.5 Gen RA
FLOOR MAT'L	2299 1/2" IMPACT	PIN DIA.			16 PLY (14)
WEARPADS	CWS (5)(6)	HYDRAULICS:		DOLLIES	2 SPEED (13)
TAPE COLOR	NONE	HOSES	TWO-4000 PSI (9)	LOCATION	D/S CRANK
LIGHT PANEL	IN GATE LED (8)	LENGTH	144"	BUMPER	UNDERRIDE GUARD
MARKER LIGHTS	20 PR TOP & BTM (7)	FITTINGS	PUSH-PULL	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	MODEL 60	HP	1" MALE	PUSH BLOCKS	YES
MUDFLAPS	YES	LP	1" FEMALE	PAINT	SILVER
HOSE HANGER	YES	HOSE LOCATION	D/S		
TIRE CARRIER	NONE	AIR & ELECTRICAL	CENTER(2)		

**REMARKS:**

1. NO INSIDE BULKHEAD STEPS.
2. EXTRA 6-WAY CONNECTOR ON NOSE TIED INTO JUNCTION BOX AT REAR JUST AHEAD OF MOST FORWARD AXLE
3. MANDOOR IN THE CENTER OF THE BULKHEAD
4. MOVE DRIVE UNIT FORWARD TO MISS TIRES OF FRONT AXLE OF FUTURE 4th STEERABLE LIFT AXLE SPACED 60" AHEAD OF FRONT OF TRIDEM
5. WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL.
6. KEITH ALUMINUM FRAME. STAINLESS STEEL HYDRAULIC TUBING. - NYLON T BLOCKS
7. 20 PAIR PER SIDE SIDE TOP & BOTTOM WITH PROTECTORS. (EVENLY SPACED)
8. ADD 1 PAIR NON LED BACK-UP LIGHTS WIRED INTO EXTRA 6-WAY IN THE TAILGATE OOX o o o XOO
9. FILTERED GLAD HANDS.
10. ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S BOTTOM RAIL.
11. RUN ALUMINUM SUBFRAME TO BACK OF LANDING GEAR
12. CROSS MEMBERS ONLY FOR FUTURE 4TH IMT/ISS SUSPENSION IMT STEERABLE LIFT AXLE 52" AHEAD OF MOST FORWARD AXLE
13. HOLLAND MARK V
14. TIREMAXX PRO PSI SYSTEM ON ALL THREE FIXED AXLES.
15. ADD AIR GAUGE (LBS.) PLUMBED TO SUSPENSION AND MOUNTED @FRONT NEAR OTHER CONNECTIONS
16. ADD DRIVE UNIT BRACING

**OVERALL HEIGHT (FT)**      **13-3**                      **EMPTY WEIGHT (#)**      **21,062**                      **CUBIC YARDS**                      **130**

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

