



# Hale Trailer Brake & Wheel

## 073359

### EAST GENESIS UNLOADER

OPEN TOP CLOSED TOP 

SERIAL # 1E1U2Y381MR073359

BODY: WEDGE DESIGN		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TRIAxLE-2 FIXED-1 LIFT
LENGTH (FEET)	48	TYPE	SPLIT VAN DOORS	TYPE	ALUM SUB FRAME(11)
HEIGHT (INCHES)	106-109	STYLE	GENESIS	AXLE TO AXLE	60" - 60"
SIDE MAT'L (OUTBOARD)	"GENESIS"	MAT'L THICKNESS	0.100	REAR AXLE SETTING	54"
FRONT 0.135		S / S HINGE ON	STD	5TH WHEEL HT	49"
MIDDLE 0.135		GATESEAL	RUBBER	PIN SETTING	36" + 1/4" KP PLATE
REAR 0.135		GATE LADDER	N/A	SUSPENSION	AAT30K/E1-2 L LIFT-E3
POLISHED SIDES	YES	TARP HOOKS	NONE	SPRINGS	AIR(16)(17)(18)(19)(20)
ROOF	NONE	WINDERS	N/A	AXLES	TP
ROOF MAT'L	NONE	GATE GUIDE	N/A	BRAKES	HEND MAXX 22T
BULKHEAD	3/16" (1)(6)(8)(9)	GATE CONTROL	DBL LOCK RODS	DUSTSHIELDS	YES
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	AIR DISC BRAKES
TARP BASKET	NONE	CROSSPIPE (S)	TWO (14) CENTER	ABS	2S / 1M
TARP	NONE		& REAR - TUBE TYPE	HUBS	10 S LW STEEL
CATWALK	YES-INTERMEDIATE				
B.H. LADDER	COMMERCIAL-D/S	COMPACTOR:		WHEELS	8.25" X 24.5"
CROSSMEMBER	"I"BEAM- 12" C/L	SIDE LATCH	N/A		(12) ALUM BUFF (21)
FLOOR MAKE	KEITH - 3.5" DRIVES	CENTER LATCH		TIRES	11R 24.5 GRABBER OA
FLOOR MAT'L	#2190 - 25 SLATS	PIN DIA.			H 16 PLY GENER.(22)
WEARPADS	24" WEAR STRIPS			DOLLIES	2 SPEED JUST ALUMILIGHT X
TAPE COLOR	NONE	HYDRAULICS:		LOCATION	D/S CRANK (23)
LIGHT PANEL	LED IN BODY (12)	HOSES	TWO-4000 PSI	BUMPER	ALUMINUM EAST UNDERRIDE
MARKER LIGHTS	LED (13)	LENGTH	108"	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	LED - MODEL 60	FITTINGS	WINGNUT	PUSH BLOCKS	VERTICAL RUBBER
MUDFLAPS	YES	HP	1" MALE	PAINT	BLACK
HOSE HANGER	YES	LP	1" FEMALE		
TIRE CARRIER	NONE	HOSE LOCATION	P/S-REF PIC BELOW		
		AIR & ELECTRICAL	CENTER (2)(3)(5)		

**REMARKS: SHOW UNIT\*\*POLISH TOP & BTM RAILS, SIDE PANELS, REAR POCKETS, T/G PANELS, JOST ALUM LG & LG WING BRACKETS**

- FOUR CAST STEPS INSIDE OF BULKHEAD OPPOSITE OUTSIDE LADDER ON D/S. HIGHEST STEP TO BE 24" DOWN FROM TOP OF THE BULKHEAD.
- RIGHT WEIGH OIL FILLED GAUGE (LBS.) MOUNTED ON NOSE TOWARDS D/S- REFERENCE PIC BELOW.
- FILTERED GLADHANDS
- ADD AUXILIARY ISO 7 WAY PLUG LABELED '7 WAY ISO'.
- MANDOOR IN CENTER OF BULKHEAD.
- TOP RAIL SECTION 99246
- KEITH ALUMINUM SUBFRAME. STAINLESS STEEL HYDRAULIC TUBING. ADD DRIVE UNIT BRACES.
- ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S BOTTOM RAIL.
- FLOOR OPENING MOVED FORWARD FOR TRIDEM, MAKE SURE DRIVE UNIT OPENING MISSES ALL AXLES, NOTE AXLE SPACING AND SETTINGS.
- EXTEND SUBFRAME AS NEEDED TO ACCOMMODATE AXLE SPACING AND HAVE ALL AXLES MISS DRIVE UNIT.
- LIGHT PANEL IN BODY AND TO HAVE LED BACK UP LIGHTS OOOX ooo XOOO
- LED - 7 PR OF 30385Y/R MARKER LIGHTS BOTTOM & TOP W/ PROTECTORS. TOP ROW 16" DOWN FROM TOP OF TOP RAIL. EVENLY PACED.
- MOVE REAR CROSSPIPE 1' FORWARD FROM STANDARD PLACEMENT.
- STANDARD NYLON T BLOCKS
- AAT30K FOR AXLES #1 & #2 AND AAL30K LIFT AXLE AS AXLE #3 (REAR AXLE) - ALL AXLES TO EQUALIZE.
- REAR LIFTING AXLE TO HAVE BRAKE RELEASE VALVE - REAR AXLE ACTUATED WITH FRAME SWITCH + ELEC CC (WIRED THROUGH AUX. PLUG)
- ALL CONTROLS TO BE IN WEATHER TIGHT POLYCARBONATE BOX AHEAD OF AXLE #1 AND WIRED FOR CC THROUGH AUX PLUG-REF.69464.
- GALVANIZED SUSPENSION HANGERS.
- NO CROSSOVER KIT FOR SUSPENSION.
- WHEEL GUARD INSULATORS.
- TIREMAXX PRO ON ALL AXLES.

OVERALL HEIGHT (FT)

13' - 5"

EMPTY WEIGHT (#)

19,526

CUBIC YARDS

136

## DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

