



# Hale Trailer Brake & Wheel

## 074200



### EAST GENESIS UNLOADER TRAILER

OPEN TOP



CLOSED TOP

**"GENESIS"**

BODY:		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TANDEM (8)(9)(10)
LENGTH (FEET)	45	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	96	STYLE	GENESIS	AXLE TO AXLE	52"
SIDE MAT'L (OUTBOARD)	"GENESIS"	MAT'L THICKNESS	0.150	REAR AXLE SETTING	26-1/2"
FRONT	0.150	S / S HINGE ON	PASS. SIDE 4-3-4	5TH WHEEL HT	49"
MIDDLE	0.150	GATESEAL	YES	PIN SETTING	36" + 3/8" KP PLATE
REAR	0.150	GATE LADDER	COMM / CENTER	SUSPENSION	AAT30K/E2/L LIFT-E1
POLISHED SIDES	NO	TARP HOOKS	NONE	SPRINGS	AIR
ROOF	NONE	WINDERS	ONE	AXLES	TP SPINDLES
ROOF MAT'L	NONE	GATE GUIDE	YES	BRAKES	16-1/2" x 7"
BULKHEAD	3/16" (1)(14)	GATE CONTROL	MECH - BOLT CLAW	DUSTSHIELDS	YES
TARP HOOKS	NONE	POCKETS	EXTRUDED	BRAKE CHAMBERS	STD
TARP BASKET	NONE	CROSSPIPE (S)	TWO - MIDDLE	ABS	2S / 1M
TARP	NONE		SPRING TYPE -	HUBS	10 S LW STEEL
CATWALK	NONE		REAR TUBE TYPE	DRUMS	LWBD
B.H. LADDER	COMMERCIAL	COMPACTOR:		WHEELS	8.25 X 24.5
CROSSMEMBER	"1"BEAM- 12" C/L	SIDE LATCH	N/A		4 STEEL/ 4 CB
FLOOR MAKE	KEITH - 3.5" DRIVES	CENTER LATCH		TIRES	11R 24.5 RA H 16 PLY
FLOOR MAT'L	#2299 - 1/2" IMPACT	PIN DIA.			GENERALS (13)
WEARPADS	CWS	HYDRAULICS:		DOLLIES	2 SPEED JOST A451
TAPE COLOR	NONE	HOSES	TWO-4000 PSI	LOCATION	D/S CRANK (6)
LIGHT PANEL	LED IN GATE(11)(12)	LENGTH	108"	BUMPER	STEEL
MARKER LIGHTS	LED (4)	FITTINGS	WINGNUT	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	LED - MODEL 60	HP	1" MALE	PUSH BLOCKS	YES
MUDFLAPS	YES	LP	1" FEMALE	PAINT	BLACK
HOSE HANGER	YES	HOSE LOCATION	DRIVER SIDE		
TIRE CARRIER	NONE	AIR & ELECTRICAL	DRIVER SIDE		

## REMARKS:

1. NO INSIDE BULKHEAD STEPS.
2. WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL.
3. KEITH ALUMINUM FRAME. STAINLESS STEEL HYDRAULIC TUBING. ADD TWO BRACES PER SIDE AT DRIVE UNIT OPENING.
4. 3 PAIR PER SIDE SIDE BOTTOM ONLY WITH PROTECTORS.
5. FILTERED GLAD HANDS.
6. ADD REGISTRATION HOLDER TO D/S LANDING GEAR BRACKET TRUCKLITE 536-05015-20.
7. ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S BOTTOM RAIL.
8. SUSPENSION IS FRONT AXLE LIFTING (ALL EQUALIZING) AND LIFT TO BE FRAME SWITCH ONLY AND IN POLYCARBONATE BOX.
9. GALVANIZED HANGERS BOTH AXLES.
10. ALL FRAME SWITCHES IN POLYCARBONATE BOX ON D/S
11. TAILLIGHTS IN THE GATE TO HAVE STROBES (S=STROBE) OOS ooo SOO WIRED TO EXTRA 7 WAY ONLY.
12. BACK UP WORK LIGHTS (BOXED IN)(WIRED TO AUXILIARY PLUG) -REARWARD OF LANDING GEAR.
13. TIREMAXX PRO TIRE INFLATION SYSTEM ON BOTH AXLES.
14. D/S-MANDOR ON BULKHEAD
15. STEM MOUNT AIR GAUGE (LBS.) PLUMBED TO SUSPENSION AND INSTALL IT IN FRONT NEAR CONNECTIONS.
16. KEITH ELECTRIC CLEEN SWEEP SYSTEM TOP BULKHEAD MOUNT (POWER SOURCE NOT INCLUDED).
17. ADD EXTRA STD 7 WAY AUXILIARY PLUG. CHANGE 1
18. ONE PAIR OF LED BACK UP LIGHTS BELOW THE GATE

OVERALL HEIGHT (FT) 12.58

EMPTY WEIGHT (#) 17, 128

CUBIC YARDS 108

( EMPTY WEIGHT VARIANCE +/- 3% )

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.