TRAIL KING

Specifications

102987-102989 (2017) "Advantage Series" Live Bottom Trailer

OLB32-102 "Advantage Series" Live Bottom Trailer
10192 - King Pin to Center of Last Axle = 31'11"
Overall Length = 36' 7"
Overall Height: (with 48" fifth wheel and no hopper extensions) 9' 2"
Overall Width = 102"
Capacity (without extensions) = 29 cubic yards
36" Direct Drive Live Floor
3" Pitch Roller Chain
2 Ply 3/8" Belt with Steel Z-Bar Support
Hydraulic Tap Chain Oiler
Liquid Filled Pressure Gauge (with air ride only)
Center Mud Flap
LED Lights

BASE

Materials Hauling:	1	OLB32-102 "Advantage Series" live bottom trailer
5 th Wheel/King Pin:	1	48" 5 th Wheel Height
Hopper Sheets:	1	Rear Hopper Sheets: .160" AR450
Hopper:	1	6" steel extensions w/tarp shelf (+ 5 cubic yards)
Exterior Sheeting:	1	Aluminum Exterior Sheeting w/insulation
Drive/ Hydraulics:	1	Single Drive (for payloads under 75,000 lbs.)
Belt/ Chain:	1	HTORS Belt
Belt/Chain:	1	Standard Chain Crossmembers (.120" Grade 80)
Tailgate/Controls:	1	Lock & Lift Air Tailgate: Electric Cab Controls
Suspensions:	1	Tri-Axle: (1) 25K Intraax Front Lift (Equalized)w/2 25K Intraax Air
Suspensions:	1	49"/50" spacing
Axles:	3	Intraax Axle (rating determined by suspension) (per axle)
Axles:	3	23K Std. Lift Brakes w/6" autoslacks (per axle)
Brakes/Air:	1	4S2M Anti- lock Brake system
Hub/Drum:	3	Duralite hub piloted-Cast drum (per axle)
Down Axle Wheels	4	8.25 x 24.5 10-hole machined aluminum wheel (per wheel) Accuride ILO std
(inside):		8.25 x 22.5 10-hole steel disc wheel
Down Axle Wheels		Alternative option selected. See additional options section below.
(outside):		Alcoa Durabrite
Lift Axle Wheels	2	8.25 x 24.5 10 hole machined aluminum wheel (per wheel) Accuride ILO Std.
(inside):		8.25 x 22.5 10 hole steel disc wheel
Lift Axle Wheels		Alternative option selected. See additional options section below.
(outside):		Alcoa Durabrite
Down Axle Tires:	8	11R24.5 Continental HSR-2 16 ply (per tire) ILO Std Tire
Lift Axle Tires:	4	11R24.5 Continental HSR-2 16 ply (per tire) ILO Std Tire
Flaps, Mud Guards &	1	Aluminum Front Fenders

Flaps, Mud Guards &	1	Aluminum Rear Fenders
Fenders:		
Flaps, Mud Guards &	1	Front Mudflaps: Short
Fenders:		
Flaps, Mud Guards &	1	Interior Mudflaps: None
Fenders:		
Flaps, Mud Guards &	1	Rear Mudflaps: post – mounted flip - up
Fenders:		
Ladder	1	Ladder Over CS Fender Std
Landing Gear:	1	Two Speed (crank road side)
Spray System:	1	No Spray System
Document Holder:	1	Document Holder: 4-1/2" round
Paint:	1	Black S7203 with White Decals (735-432-039)
Decals:	1	Black Logo and Stripe

<u>10192 – ADDITIONAL OPTIONS</u>

Lights/Electrical	1	Dual Halogen Spotlights Std
Axles	3	P spindles (required w/super single tires) Per axle
Axles	3	Dust Shields (per axle)
Lights/Electrical	1	Dual Strobe Lights (std location)
Lights/Electrical	1	Back Up alarm 107db Std.
Wheels	6	8.25 x 24.5 Aluminum Alcoa Dura Brite (per wheel)