

TRAILKING

106058

2015

TKPA1 Flip Axle (REAR PIN-ON AXLE)

10988-STANDARD EQUIPMENT

Pan Style Design

Air Ride Suspension

Automatic Slack Adjusters

8.25 x 22.5 10 Hole Disc Wheel

One-piece axle seals

Pro Tork Axle Nuts

LED Lights, 50 State Legal

Electrical System per DOT Regulations

Flagholders

Rubber Mounted Sealed Lights with sealed
Harness System

Mudflaps

Red and White Conspicuity Markings

Paint: Trail King 2-part Polyurethane

TKPA1 Flip Axle (Rear Pin-On Axle)-Identical to D1922-Lift Brackets (2) D-rings on front face

60" Axle Spacing

Overall width: Alternative Option Selected. See Below

Beam Depth: For correct Flip Axle beam depth, specify the Serial # of the corresponding trailer.
Goes w/ 120LPSD

Position: Rear flip axle

Delete D-rings from rear channel (there is no rear channel on this unit)

Flip Axle Styles: Alternative Option Selected. See Additional Options Section Below.

Non-loadbearing wheel covers.

Upper Bracket Style: Upper Links for trailers other than HDG ADV Plus

Axles: 27,000 lb. (3/4" wall) axle

Brakes: Alternative Option Selected. See Additional Options Section Below.

Hub/Drum: Steel Hub-piloted-Cast Drum.

Wheel Finish (inside): Steel Wheels

Wheel Finish (outside): 6.75 x 17.5-16 ply in lieu of STD. STD. Steel Wheels (2)

Tire Size: 235/75R17.5 16 ply in lieu of STD. 255/70R22.5 16 ply (4)

Lights/Electrical: Alternative Option Selected. See Additional Options Sections Below.

Paint: Black S7203 w/white decals (735-432-039)

Additional Options:

Custom Options: #60690 TKFA1 Flip Axle 10' wide

Custom Options: #61376 TKFA1 6.75 x 17.5 8-hole disc wheels

Brackets at rear of push/tow bar

Wheel Finish (outside): 6.75 x 17.5 polished aluminum ILO Std. steel wheels (2)

Tire Size: 235/75R 17.5-16 ply ILO of STD 255/70R 22.5-16 ply (4)

GOES WITH 6056 & 6057, 60T

Disclaimer

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are representative of the subject equipment, but may not be identical. Equipment availability, prices & specifications are subject to change without notice.