

ETNYRE

Specifications

111389
2015

Widespread Capable Lowboy

Goes with Flip Box Q314071
Intermediate Flip Axles 111391, 111390
Rear Flip Axle 111239
Spreader Bar Q314075

| | |
|----------------------------------|---|
| Model: | RTN65TD-R3/4/5A-RA Trailer |
| Tons Capacity: | 65 Tons in any 16' |
| Construction: | (4) I-beam, cambered, T-1 Steel |
| Dropside Deck: | 16 3/4" side height (wood filled) |
| Platform Width: | 8' 6" |
| Platform Length: | 30' (Future 10' deck insert) |
| Platform Height/Road Clearance: | 24"/6" 18" deep main beams |
| Crossmember Spacing: | On 20" centers |
| Front Folding Ramps: | Steel with traction bars |
| Frame Reinforcement: | For a 3+2 (14'-1" spread) |
| Top Flange Reinforcement: | Outside main beams only |
| Bucket Trough: | Last 3 crossmembers in deck |
| Detachable Rear Section: | For decks & shimming |
| Hydraulic System: | From tractor wet line |
| 20' Gooseneck: | Non-ground engaging removable hi lift |
| Gooseneck Support Cylinder: | Hydraulic |
| Gooseneck Connection: | Pin & Stirrup type with vertical air lock pin |
| Swing Clearance: | 120" and 108" king pin setting with future 70" extension |
| 5 th Wheel Height: | 48"-50"-52"-54"-56" loaded (adjustable) |
| 1/8" Aluminum Top Cover: | Over gooseneck area |
| Air Brakes: | 16.5" x 7" with auto slacks and outboard drums |
| Anti-Lock Brakes: | None (Trailer GVWR exceeds 120,000#) |
| Spring Brakes: | On one axle |
| Axles: | (2) 25,000# 3/4" wall with 25,000# brakes |
| Tires: | (8) 275/70R 22.5 (H) |
| Wheels: | Steel disc, 10-Hole, hub piloted, 8.25" x 22.5" |
| Suspension: | 30,000# Air ride with 60.5" axle spacing +3/-3 Height control, auto/manual |
| Manual Exhaust Valve: | Knob style |
| Raising & Lowering Valves: | At Rear of trailer and both flips |
| Liquid Filled Air Gauge: | At rear of trailer and both flips |
| Lights: | LED Trucklite rubber sealed system |
| Flasher Kit: | With rechargeable battery feature (Flash all lights) |
| Amber LED Strobes: | Rear of trailer & both flips |
| Air & Electrical: | At rear for future axles |
| Lash Rings: | (20) Total, 10 per side, bent style |
| Extension Brackets (Outriggers): | 12" Swing/removable with double hook-on front |

Disclaimer

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are representative of the subject equipment, but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

| | |
|---------------------------------|---|
| Decking: | 2" Apitong (Outside main beams only) |
| Paint: | Black (2-Part urethane) |
| Boomwell: | Open bottom with extra low 1 st crossmember (No cover plate) |
| Chain Hook & Flag Holder Slots: | On bolsters |
| Estimated Weight: | 30,800#(+/-5%) |

Disclaimer

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are representative of the subject equipment, but may not be identical. Equipment availability, prices and specifications are subject to change without notice.