

TRAIL KING

Specifications

113019-113021

(2017) “Advantage Series” Live Bottom Trailer

OLB32-102 “Advantage Series” Live Bottom Trailer
10192 - King Pin to Center of Last Axle = 31’11”
Overall Length = 36’ 7”
Overall Height: (with 48” fifth wheel and no hopper extensions) 9’ 2”
Overall Width = 102”
Capacity (without extensions) = 29 cubic yards
36” Direct Drive Live Floor
3” Pitch Roller Chain
2 Ply 3/8” Belt with Steel Z-Bar Support
Hydraulic Tap Chain Oiler
Liquid Filled Pressure Gauge (with air ride only)
Center Mud Flap
LED Lights

BASE

Materials Hauling:	1	OLB32-102 “Advantage Series” live bottom trailer
5 th Wheel/King Pin:	1	48” 5 th Wheel Height; Removable King Pin
Hopper Sheets:	1	Rear Hopper Sheets: .160” AR450
Hopper:	1	6” steel extensions w/tarp shelf (+ 5 cubic yards)
Exterior Sheeting:	1	Aluminum Exterior Sheeting w/insulation
Drive/ Hydraulics:	1	Single Drive (for payloads under 75,000 lbs.)
Belt/ Chain:	1	HTORS Belt
Belt/Chain:	1	Standard Chain Crossmembers (.120” Grade 80)
Tailgate/Controls:	1	Lock & Lift Air Tailgate: Electric Cab Controls
Suspensions:	1	Tri-Axle: (1) 25K Intraax front lift (equalized) w/(2) 25K Intraax Air
Suspensions:	1	49”/50” spacing
Axles:	3	Intraax Axle (rating determined by suspension)(per axle)
Axles:	3	23K Standard Lift Brakes w/6” Autoslacks (per axle)
Brakes/Air:	1	4S2M Anti- lock Brake system
Hub/Drum:	3	Duralite hub piloted – cast drum (per axle)
Down Axle Wheels (inside):	4	8.25 x 24.5 10-hole machined aluminum wheel (per wheel) Accuride ILO std 8.25 x 22.5 10-hole steel disc wheel
Down Axle Wheels (outside):	4	8.25 x 24.5 10-hole polished aluminum wheel (per wheel) Accuride ILO std 8.25 x 22.5 10-hole steel disc wheel
Lift Axle Wheels (inside):	2	8.25 x 24.5 10-hole machined aluminum wheel (per wheel) Accuride ILO Std. 8.25 x 22.5 10-hole steel disc wheel
Lift Axle Wheels (outside):	2	8.25 x 24.5 10-hole machined aluminum wheel (per wheel) Accuride ILO Std. 8.25 x 22.5 10-hole steel disc wheel
Down Axle Tires:	8	11R24.5 Continental HSR-2 16 ply (per tire) ILO Std Tire
Lift Axle Tires:	4	11R24.5 Continental HSR-2 16 ply (per tire) ILO Std Tire

Disclaimer

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are representative of the subject equipment, but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

Flaps, Mud Guards & Fenders:	1	Aluminum Front Fenders
Flaps, Mud Guards & Fenders:	1	Aluminum Rear Fenders
Flaps, Mud Guards & Fenders:	1	Front Mudflaps: Short
Flaps, Mud Guards & Fenders:	1	Interior Mudflaps: None
Flaps, Mud Guards & Fenders:	1	Rear Mudflaps: post – mounted flip - up
Landing Gear:	1	Two Speed (crank road side)
Spray System:	1	No Spray System
Document Holder:	1	Document Holder: 4-1/2” round
Tarps:	1	Aero “Crank-N-Go” Tarp, Electric
Lights/Electrical:	1	LED Lights-DOT Required w/Midturn
Paint:	1	Black S7203 with White Decals (735-432-039)
Decals:	1	Black Logo and Stripe

08599 – ADDITIONAL OPTIONS

Axles:	3	P Spindles (required w/super single tires) (per axle)
Lights/Electrical	1	Dual Halogen Spotlights Std.
Lights/Electrical	1	Dual Strobe Lights (Std. location)
Axles:	3	Dust shields (per axle)
Lights/Electrical:	1	Back-up alarm – 107 db (std)

Disclaimer

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are representative of the subject equipment, but may not be identical. Equipment availability, prices and specifications are subject to change without notice.