

# TRAIL KING

## Specifications

125935 - 125939

(2018) “Advantage Series” Heavy Duty Live Bottom Trailer

OLB36NGH “Advantage Series” Heavy Duty live bottom trailer
08599 - King Pin to Center of Last Axle = 35’ 11”
Overall Length = 40’ 9”
Overall Height: (with 48” fifth wheel and no hopper extensions) 10’ 2”
Overall Width = 102”
Capacity (without extensions) = 40 cubic yards
36” Direct Drive Live Floor
3” Pitch Roller Chain
2 Ply 3/8” Belt with Steel Z-Bar Support
Hydraulic Tap Chain Oiler
Liquid Filled Pressure Gauge (with air ride only)
Heavy Duty Push Block
Center Mud Flap

### BASE

Materials Hauling:	1	OLB36NGH “Advantage Series” Heavy Duty live bottom trailer
5 <sup>th</sup> Wheel/King Pin:	1	48” 5 <sup>th</sup> Wheel Height
5 <sup>th</sup> Wheel/King Pin:	1	Removable Kingpin
Hopper Sheets:	1	Full Hopper Sheets: .160” AR450
Hopper Extensions:	1	No extensions w/universal tarp shelf
Exterior Sheeting:	1	Aluminum Exterior Sheeting
Drive/ Hydraulics:	1	Alternative option selected. See Add’l Options Section Below.
Belt/ Chain:	1	HTORS Belt
Belt/Chain:	1	Heavy Duty Chain Crossmembers (.160” Domex 100)
Tailgate/Controls:	1	Lock & Lift Air Tailgate: Electric Cab Controls
Suspensions:	1	Quad Axle: (1) 25k steerable front lift w/ (3) HD Spring 211b)
Suspensions:	1	Alternative option selected. See Add’l Options Section Below.
Axles:	3	3/4” Wall Axle- 27,000lb nominal rating (per axle)
Axles:	4	23k Standard Life Brakes with 6” Autoslacks (per Axle)
Brakes/Air:	1	2S1M / 2S2M Anti- lock Brake system
Brakes/ Air:	1	Alternative option selected. See Add’l Options Section Below.
Hub/Drum:	3	Duralite hub-piloted – cast drum (per axle)
Down Axle Wheels (inside):	6	8.25 x 24.5 10-hole machined aluminum wheel (per wheel)Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel
Down Axle Wheels (outside):	6	8.25 x 24.5 10-hole polished aluminum wheel (per wheel) Accuride ILO Std 8.25 x 22.5 10-hole steel disc wheel
Lift Axle Wheels (inside):	1	No inside wheel required. (outside wheels are super singles)
Lift Axle Wheels	2	12.25 x 22.5 aluminum polished .56” offset (per wheel)Accuride ILO

### Disclaimer

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are representative of the subject equipment, but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

(outside):		Std 8.25 x 22.5 10-hole steel disc wheel
Down Axle Tires:	12	11R24.5 Continental HSR-2 16 ply (per tire) ILO Std Tire
Lift Axle Tires:	2	385/65R22.5 Continental HTR-2 20 Ply (per tire) ILO Std Tire
Ladder:	1	Ladder over CS fender (std location)
Lights & Electrical:	1	LED lights – DOT required with midturn
Tarps:	1	Shurco “Shur Trak” Tarp, Electric
Flaps, Mud Guards & Fenders:	1	Aluminum Front Fenders
Flaps, Mud Guards & Fenders:	4	Plastic Half-Round Rear Fenders (per axle)
Flaps, Mud Guards & Fenders:	1	Front Fender Mudflaps: Short Front, Long Rear
Flaps, Mud Guards & Fenders:	1	Rear Mudflaps: post-mounted flip - up
Flaps, Mud Guards & Fenders:	1	Interior Mudflaps: None
Landing Gear:	1	Two Speed (crank road side)
Spray System:	1	No Spray System
Document Holder:	1	Document Holder: 12” x 14” flat
Paint:		Black S7203 with White Decals (735-432-039)
Decals:	1	Black logo and stripe

#### **08599 – ADDITIONAL OPTIONS**

Axles:	4	P Spindles (required w/super single tires) (per axle)
Lights/Electrical:	1	Dual Halogen Spotlights (std location)
Lights/Electrical:	1	Dual strobe lights (std location)
Lights/Electrical:	1	Back-up alarm – 107 db (std location)
Special	1	80480 (OLBNG-HH) 121”/50”/49” Axle Spacing
Custom Options	1	81626 (All OLB) No Automatic Reverse Control – Steerable Axle
Custom Options	1	81633 (OLBHH) 19.0cu. Hydraulic Motor ILO std 15.0cu. in Hydraulic Motor

#### Disclaimer

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are representative of the subject equipment, but may not be identical. Equipment availability, prices and specifications are subject to change without notice.