FONTAINE

Specifications

2018 "VELOCITY" HAVSF12SAT STEEL FLAT 527853 - 527867

48'

Length: Width: Suspension Type: Frame Rating: Flooring: Crossmembers: Side Rails: Stake Pockets: Pipe Spools: Rubrail: Main Beams: Kingpin: Loaded 5th Wheel Height: Landing Gear: Knee Braces: Bulkheads: Bulkhead Pockets: Number of Axles: Axle Spindle: Brakes: Air Line Filters: ABS. Axle Spread: Hub and Drums: Wheel Ends: Wheels: Tires: Tire Inflation System: Suspension Detail: Air Asist Slide Box Pins: Auto Glad Hand Dump: Front Corners: Electrical System: Paint: Conspicuity Tape: Bumper: Mud Flaps: Spare Tire Carrier: Winch Track: Sliding Winches: Winch Straps: Dock Bumpers: Hubodometer: **Registration Holder:** Tool Box: VIN Plate: Total Weight:

102" Sliding Air Tandem 80,000 lbs. distributed-GAWR and tire ratings determine legal payloads 1 1/8" wood 12" centers - 4" Jr. I-steel 6" structural channel @ 6.5 lbs/ft 3/16" steel on 24" centers Double between stake pockets 3/8" x 2 $\frac{1}{2}$ " steel 130k load bearing flanges 30" 49" OEM standard Fabricated on approx. 60" c/c Removable steel bulkhead - no turn back - 48" high 4 – F-5 DOT-type steel 2 Tapered Spring brakes, auto slacks (2) Meritor In-line type installed 4S/2M – no cable or tool 49" 10-hole hub-piloted with outboard cast drums Grease in hubs - ***5 year wheel end warranty*** 22.5 x 8.25 steel disc wheels - pre-painted white-STD 11R 22.5 14PR OEM standard tires None standard Hendrickson AAZNT46K Intraax air ride slider - 60" adjustable Standard mount of controls on slider frame Installed Tapered LED: 3 lights/side, 2 lights/side on rear-STD Black urethane with Velocity decals - standard Per NHTSA specs - installed on rubrails Weld on type - meets under ride requirements 1 set OEM Std. None standard Steel on road side 12 standard – without straps None Std. 1 pair rubber on rear None standard Install registration holder-OEM Std. None standard Bilingual US/Canadian VIN plate 12,411# +/-3%

DISCLAIMER