

# FONTAINE

## DETACHABLE DOUBLE DROP EXTENDABLE

MODEL: RENEGADELXT40 (Renegade LXT40 Air Tandem)

2018

574169 - 574172

|                                     |  |
|-------------------------------------|--|
| Capacity:                           | 40 Tons in 16' length – GAWR and tire ratings determine legal loads  |
| Load Base:                          | 16' rigid 2-point load centered in deck  |
| Framework:                          | All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs   |
| Compatibility:                      | Designed to accept optional flip neck extension and third flip axle  |
| Length/width:                       | 47 feet 11 inches **see deck length options – 102 inches wide  |
| Gooseneck Design:                   | Mechanical removable with removable fifth wheel guide rollers – combination figure – 8 plate which provides 50 inches and 52 inches loaded – swing radius of 81 inches |
| Gooseneck platform:                 | Full width gooseneck platform with 1 1/8 inch wood floor   |
| Flip box:                           | None   |
| Tool box:                           | None   |
| Gooseneck fenders:                  | Aluminum fenders at rear of gooseneck  |
| Electrical Receptacle:              | J560 7-pin connector   |
| Deck Design:                        | Flat level telescopic deck design  |
| Deck Length:                        | 34 feet 0 inches clear deck length (retracted) – 60 feet 0 inches (extended) **Note trailer overall length is 53 feet  |
| Loaded Deck Height:                 | 20" with 6" ground clearance   |
| Flooring:                           | 1 3/8" nominal wood (full width)   |
| Recessed Floor Mounted D-Ring       | None   |
| Package:                            |  |
| Crossmembers:                       | On 24" centers   |
| Front Ramps:                        | None, front of deck sloped top down to assist in loading with traction cleats  |
| Extension Brackets:                 | Mounting brackets only   |
| Front Bogie Ramp:                   | Sloped steel bogie ramp (full width)   |
| Mini Boom Trough & traction Cleats: | None   |
| Deck to Bogie Connection:           | Fixed  |
| Number of Axles:                    | 2  |
| Axle Capacity:                      | 25,000# nominal capacity per axle Note: GAWR determined by suspension type, brakes, tires and other components   |
| Axle Spread:                        | 54.5" spread (between axles)   |
| Brakes:                             | 16.5" x 7" with 5.5" auto slacks – heavy duty brake drums – outboard mount   |
| Dust Shields:                       | None   |
| Spring Brakes:                      | Spring brakes on 2 axles   |
| Suspension:                         | Air ride with automatic controls   |
| First axle lift:                    | Chain lift included on first axle when 34ft deck is selected   |
| Tires:                              | 255/70R 22.5 H ply OEM standard  |
| Wheels:                             | 8.25 x 22.5 steel disc - hub piloted   |
| Covered Rear Bogie:                 | Rear bogie platform with 1 1/8" wood floor   |
| Rear Bogie Height:                  | 41"  |
| Bumper:                             | 3 tail light package   |
| Connections for Future Axle         | Air and electrical connections to go along with connecting ears  |
| Attachment:                         |  |
| Width:                              | 8' 6"  |
| Electrical System:                  | DOT sealed beam and harness with LED lights  |
| Flip Axle:                          | None   |
| Dust shields on flip axle:          | None   |

### DISCLAIMER

SPECIFICATIONS ARE BELIEVED TO BE CORRECT, BUT MAY CONTAIN ERRORS AND/OR OMISSIONS. PHOTOGRAPHS ARE REPRESENTATIVE OF THE SUBJECT EQUIPMENT, BUT MAY NOT BE IDENTICAL. EQUIPMENT AVAILABILITY, PRICES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

|                                |  |
|--------------------------------|--|
| Flip Axle Strobe Light Kit:    | None   |
| Paint:                         | Fontaine BLACK polyurethane enamel             |
| Lash Rings:                    | 9 Pair – 18 Total                              |
| Flag Holders:                  | 3 pair flag holders                            |
| ABS:                           | 4S/2M system without diagnostic tool and cable |
| Liquid Filled Gauge:           | Included                                       |
| Marker Lights:                 | 8 Marker lights per side including mid-turn    |
| Accent Package:                | Stainless steel accent package                 |
| VIN Plate:                     | Bilingual VIN plate                            |
| Registration/ Document Holder: | Install registration/document holder           |
| Estimated Weight:              | 21,315# +/-3%                                  |

**DISCLAIMER**

SPECIFICATIONS ARE BELIEVED TO BE CORRECT, BUT MAY CONTAIN ERRORS AND/OR OMISSIONS.  
PHOTOGRAPHS ARE REPRESENTATIVE OF THE SUBJECT EQUIPMENT, BUT MAY NOT BE IDENTICAL.  
EQUIPMENT AVAILABILITY, PRICES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.